

ADDINOL Lube Oil GmbH

according to Regulation (EC) No 1907/2006

#### **ADDINOL Eco Gear 320 W**

Print date: 10.11.2014 Product code: 741077 Page 1 of 8

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

ADDINOL Eco Gear 320 W

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Gearbox oil.

#### 1.3. Details of the supplier of the safety data sheet

Company name: ADDINOL Lube Oil GmbH

Gebäude 4609

Street: Am Haupttor
Place: D-06237 Leuna

Telephone: +49 (0) 3461 845-201 Telefax: +49 (0) 3461 845-561

e-mail: info@addinol.de

Contact person: Application Technology

Internet: www.addinol.de

Responsible Department: ADDINOL Application Technology

1.4. Emergency telephone +49 (0) 3461 845-201 - This number is serviced during office hours.

number:

#### **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

The preparation is not dangerous in the sense of Directive 1999/45/EC.

This mixture is classified as not hazardous according to Regulation (EC) 1272/2008 [GHS].

## 2.2. Label elements

## Special labelling of certain mixtures

EUH208 Contains N,N-di(2-ethylhexyl)-4-methyl-1H-benzotriazole-1-methanamine. May produce

an allergic reaction.

EUH210 Safety data sheet available on request.

### 2.3. Other hazards


Prolonged/repetitive skin contact may cause skin defattening or dermatitis.

Spilled product must not leak into the ground.

Do not allow uncontrolled leakage of product into the environment.

## **SECTION 3: Composition/information on ingredients**

## 3.2. Mixtures





according to Regulation (EC) No 1907/2006

#### **ADDINOL Eco Gear 320 W**

Print date: 10.11.2014 Product code: 741077 Page 2 of 8

#### **Hazardous components**

EC No	Chemical name	Quantity
CAS No	Classification	
Index No	GHS classification	
REACH No		
296-404-1	Phosphoric acid esters, amine salt	< 0,25 %
92623-72-8	Xi - Irritant, N - Dangerous for the environment R41-51-53	
	Eye Dam. 1, Aquatic Chronic 2; H318 H411	
279-503-4	N,N-di(2-ethylhexyl)-4-methyl-1H-benzotriazole-1-methanamine	< 0,25 %
80584-90-3	Xi - Irritant, N - Dangerous for the environment R38-43-51-53	
	Skin Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H315 H317 H411	
279-514-4	N,N-bis(2-ethylhexyl)-5-methyl-1H-benzotriazole-1-methylamine	< 0,25 %
80595-74-0	Xi - Irritant, N - Dangerous for the environment R38-43-51-53	
	Skin Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H315 H317 H411	
200-659-6	methanol	< 0,25 %
67-56-1	F - Highly flammable, T - Toxic R11-23/24/25-39/23/24/25	
603-001-00-X	Flam. Liq. 2, Acute Tox. 3, Acute Tox. 3, Acute Tox. 3, STOT SE 1; H225 H331 H311 H301 H370 **	
260-991-2	Calcium dinonylnaphthalene sulphonate	< 0,25 %
57855-77-3	Xi - Irritant R36/38	
	Skin Irrit. 2, Eye Irrit. 2; H315 H319	

Full text of R and H phrases: see Section 16.

### **Further Information**

DMSO-Extrakt < 3 %, IP 346.

Concentration of PCBs < 1mg/kg.

Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

## **SECTION 4: First aid measures**

# 4.1. Description of first aid measures

## **General information**

Self-protection of the first aider.. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

#### After inhalation

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist.

#### After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. In case of skin irritation, seek medical treatment.

## After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

## After ingestion

Do not induce vomiting. Rinse mouth immediately and drink large quantities of water. Immediately get medical attention.



ADDINOL Lube Oil GmbH

according to Regulation (EC) No 1907/2006

#### **ADDINOL Eco Gear 320 W**

Print date: 10.11.2014 Product code: 741077 Page 3 of 8

### 4.2. Most important symptoms and effects, both acute and delayed

No information available.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

#### Suitable extinguishing media

Foam. Extinguishing powder. Carbon dioxide (CO2). Atomized water.

#### Unsuitable extinguishing media

High power water jet.

#### 5.2. Special hazards arising from the substance or mixture

Can be released in case of fire: Carbon monoxide. Carbon dioxide (CO2). Sulfur oxides. Phosphorus oxides. Nitrogen oxides (NOx). Carbon black.

#### 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

#### Additional information

Extinguishing materials should be selected according to the surrounding area. Use water spray/stream to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

High slip hazard because of leaking or spilled product. Remove all sources of ignition. Wear respiratory protection when in the presence of vapour, dust, and aerosols.

#### 6.2. Environmental precautions

Do not empty into drains or the aquatic environment. In case of gas being released or leakage into waters, ground or the drainage system, the appropriate authorities must be informed. Prevent spreading over great surfaces (e.g. by damming or installing oil booms).

## 6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the assimilated material according to the section on waste disposal. Clean contaminated objects and areas thoroughly observing environmental regulations.

## 6.4. Reference to other sections

Refer to the provisions listed in Sections 8, 12 and 13.

#### **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

## Advice on safe handling

Work in well ventilated zones or use proper respiratory protection. Avoid oil mist In case of open handling equipment with built-in suction must be used. Avoid contact with skin, eye and clothing.

## Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

## 7.2. Conditions for safe storage, including any incompatibilities

## Requirements for storage rooms and vessels

Keep the packing dry and well sealed to prevent contamination and absorbtion of dampness.

## Advice on storage compatibility

Keep away from food, drink and animal feedingstuffs.



ADDINOL Lube Oil GmbH

according to Regulation (EC) No 1907/2006

#### **ADDINOL Eco Gear 320 W**

Print date: 10.11.2014 Product code: 741077 Page 4 of 8

Keep away from: Oxidizing agents. Reducing agents. Peroxides.

## Further information on storage conditions

Recommended storage temperature: 10 - 30°C Protect against: heat. UV-radiation/sunlight.

#### 7.3. Specific end use(s)

Further information: refer to Technical Data Sheet.

## **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters

### Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
67-56-1	Methanol	200	260		TWA (8 h)	
		-	-		STEL (15 min)	

#### **Biological limit values**

CAS No	Substance	Parameter	Value	Test material	Sampling time
67-56-1	Methanol	Methanol	15 mg/L	Urine	End of shift

#### Additional advice on limit values

Recommended limit value for oil mist

TWA: 5 mg/m<sup>3</sup> STEL: 10 mg/m<sup>3</sup>

The product does not contain any relevant quantities of substances with legally established exposure limitation.

## 8.2. Exposure controls





## Appropriate engineering controls

Provide for sufficient ventilation and punctiform suction at critical points.

## Protective and hygiene measures

Wash hands before breaks and at the end of work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

### Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): DIN EN 166

#### Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): DIN EN 374

Duration of wearing with permanent contact: 480 min

Suitable material: NBR (Nitrile rubber). Thickness of glove material: 0.7 mm.

Duration of wearing with occasional contact (splashes): 30 min

Suitable material: NBR (Nitrile rubber). Thickness of glove material: 0.4 mm



ADDINOL Lube Oil GmbH

according to Regulation (EC) No 1907/2006

#### **ADDINOL Eco Gear 320 W**

Print date: 10.11.2014 Product code: 741077 Page 5 of 8

Protect skin by using skin protective cream.

#### Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

## Respiratory protection

If technical suction or ventilation measures are not possible or are insufficient, protective breathing apparatus must be worn.

# **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Physical state: liquid
Colour: yellow
Odour: characteristic

**Test method** 

## Changes in the physical state

Initial boiling point and boiling range: not determined

Flash point: > 250 °C DIN ISO 2592

Ignition temperature: not determined

Density (at 15 °C): 0,854 g/cm³ DIN 51757

Water solubility: virtually insoluble

Viscosity / kinematic: 300 mm²/s DIN 51562

(at 40 °C)

## **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

Stable with proper care and handling.

# 10.2. Chemical stability

The product is chemically stable when handled and stored under normal conditions.

#### 10.4. Conditions to avoid

Do not overheat to avoid decomposition by heat. Refer to chapter 7 No further action is necessary.

## 10.5. Incompatible materials

Reacts with: Oxidizing agents, strong. Reducing agents. Peroxides.

#### 10.6. Hazardous decomposition products

Can be released in case of fire: Carbon monoxide. Carbon dioxide (CO2). Sulfur oxides. Phosphorus oxides. Nitrogen oxides (NOx). Carbon black.


# **SECTION 11: Toxicological information**

## 11.1. Information on toxicological effects

#### **Acute toxicity**

No data available

Preparation not tested.





according to Regulation (EC) No 1907/2006

#### **ADDINOL Eco Gear 320 W**

Print date: 10.11.2014 Product code: 741077 Page 6 of 8

CAS No	Chemical name					
	Exposure routes	Method	Dose	Species	Source	
80584-90-3	N,N-di(2-ethylhexyl)-4-methyl-1H-benzotriazole-1-methanamine					
	oral	LD50	2.000 mg/kg	Rat.		
67-56-1	methanol					
	oral	ATE	100 mg/kg			
	dermal	ATE	300 mg/kg			
	inhalative vapour	ATE	3 mg/l			
	inhalative aerosol	ATE	0,5 mg/l			

#### Irritation and corrosivity

Evaluation: Irritating to eyes and skin.

#### Sensitising effects

 $Contains: <0.25\%\ N, N-di(2-ethylhexyl)-4-methyl-1 H-benzotriazole-1-methanamine.$ 

May produce an allergic reaction.

#### Severe effects after repeated or prolonged exposure

Prolonged/repetitive skin contact may cause skin defattening or dermatitis.

#### Carcinogenic/mutagenic/toxic effects for reproduction

No data available

#### Specific effects in experiment on an animal

No data available

# **SECTION 12: Ecological information**

## 12.1. Toxicity

No data available

Preparation not tested.

# 12.2. Persistence and degradability

Not easily bio-degradable (according to OECD-criteria). Do not empty into drains or the aquatic environment.

# 12.3. Bioaccumulative potential

No data available

#### 12.4. Mobility in soil

Due to its low solubility in water the product is almost completely mechanically separated in biological waste water treatment plants.

## 12.5. Results of PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

### 12.6. Other adverse effects

No data available

### **Further information**

Do not allow uncontrolled leakage of product into the environment.

# **SECTION 13: Disposal considerations**

# 13.1. Waste treatment methods

## Advice on disposal

Must not be disposed of with domestic refuse. Do not empty into drains or the aquatic environment.



ADDINOL Lube Oil GmbH

according to Regulation (EC) No 1907/2006

#### **ADDINOL Eco Gear 320 W**

Print date: 10.11.2014 Product code: 741077 Page 7 of 8

#### Waste disposal number of waste from residues/unused products

130206 OIL WASTES AND WASTES OF LIQUID FUELS (except edible oils, and those in chapters 05, 12 and

19); waste engine, gear and lubricating oils; synthetic engine, gear and lubricating oils

Classified as hazardous waste.

#### Contaminated packaging

Contaminated packing must be completely emptied and can be re-used following appropriate cleaning. Packing which cannot be properly cleaned must be thrown away. Waste disposal according to official state regulations.

## **SECTION 14: Transport information**

### Land transport (ADR/RID)

<u>14.1. UN number:</u> -

Inland waterways transport (ADN)

14.1. UN number: -

Marine transport (IMDG)

<u>14.1. UN number:</u> -

Air transport (ICAO)

<u>14.1. UN number:</u> -

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

## 14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

#### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

not applicable

## Other applicable information

Not a hazardous material with respect to these transportation regulations.

# **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **National regulatory information**

Water contaminating class (D): 1 - slightly water contaminating

## 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

# **SECTION 16: Other information**

### Full text of R phrases referred to under Sections 2 and 3

11 Highly flammable.

23/24/25 Toxic by inhalation, in contact with skin and if swallowed.

36/38 Irritating to eyes and skin.

38 Irritating to skin.

39/23/24/25 Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if

swallowed.

41 Risk of serious damage to eyes.

43 May cause sensitisation by skin contact.

51 Toxic to aquatic organisms.

May cause long-term adverse effects in the aquatic environment.



according to Regulation (EC) No 1907/2006

#### **ADDINOL Eco Gear 320 W**

Print date: 10.11.2014 Product code: 741077 Page 8 of 8

### Full text of H statements referred to under Sections 2 and 3

H225	Highly flammable liquid and vapour.
H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H370	Causes damage to organs.

#### **Further Information**

H411

This mixture is classified as not hazardous according to Regulation (EC) 1272/2008 [GHS].

Toxic to aquatic life with long lasting effects.

These given data only refer to the named product. If the product is used together with other materials or in manufacturing processes the data might not be applicable any more. The data are based on today's state of our knowledge and experience. They are, however, no guarantee of any specific product properties and do not established any legally valid contructual relationship.

The receiver of our product is singulary responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)