



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### ADDINOL Gear Oil CKT 150

Print date: 09.02.2015

Product code: 741096

Page 1 of 8

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

ADDINOL Gear Oil CKT 150

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

###### Use of the substance/mixture

Gearbox oil.

##### 1.3. Details of the supplier of the safety data sheet

Company name:	ADDINOL Lube Oil GmbH	
	Gebäude 4609	
Street:	Am Haupttor	
Place:	D-06237 Leuna	
Telephone:	+49 (0) 3461 845-201	Telefax: +49 (0) 3461 845-561
e-mail:	info@addinol.de	
Contact person:	Application Technology	
Internet:	www.addinol.de	
Responsible Department:	ADDINOL Application Technology	

##### 1.4. Emergency telephone number:

+49 (0) 3461 845-201 - This number is serviced during office hours.

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

This mixture is classified as not hazardous according to Regulation (EC) 1272/2008 [GHS].

The preparation is not dangerous in the sense of Directive 1999/45/EC.

##### 2.2. Label elements

###### Special labelling of certain mixtures

EUH208	Contains Long-chained alkyl amine. May produce an allergic reaction.
EUH210	Safety data sheet available on request.

##### 2.3. Other hazards

Prolonged/repetitive skin contact may cause skin defatting or dermatitis.  
Spilled product must not leak into the ground.  
Do not allow uncontrolled leakage of product into the environment.

#### SECTION 3: Composition/information on ingredients

##### 3.2. Mixtures

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**ADDINOL Gear Oil CKT 150**

Print date: 09.02.2015

Product code: 741096

Page 2 of 8

**Hazardous components**

EC No	Chemical name	Quantity
CAS No	Classification	
Index No	GHS classification	
REACH No		
	Long-chained alkyl amine	
n.a.	T - Toxic, C - Corrosive, N - Dangerous for the environment R22-23/24-34-43-48/23-50-53	< 0,15 %
	Acute Tox. 2, Acute Tox. 3, Acute Tox. 4, Skin Corr. 1B, Skin Sens. 1, Aquatic Acute 1, Aquatic Chronic 1; H330 H311 H302 H314 H317 H400 H410	
	Alkyl phosphonate	< 0,15 %
n.a.	Xi - Irritant, N - Dangerous for the environment R38-41-51-53	
	Skin Irrit. 2, Eye Dam. 1, Aquatic Chronic 2; H315 H318 H411	

Full text of R and H phrases: see Section 16.

**Further Information**

DMSO-Extrakt &lt; 3 %, IP 346.

Concentration of PCBs &lt; 1mg/kg.

Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

**SECTION 4: First aid measures****4.1. Description of first aid measures****General information**

Self-protection of the first aider.. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

**After inhalation**

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist.

**After contact with skin**

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. In case of skin irritation, seek medical treatment.

**After contact with eyes**

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

**After ingestion**

Do not induce vomiting.

Rinse mouth thoroughly with water. Immediately get medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**

No information available.

**4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptomatically.

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**Foam. Extinguishing powder. Carbon dioxide (CO<sub>2</sub>). Atomized water.



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### ADDINOL Gear Oil CKT 150

Print date: 09.02.2015

Product code: 741096

Page 3 of 8

**Unsuitable extinguishing media**

High power water jet.

**5.2. Special hazards arising from the substance or mixture**

Can be released in case of fire: Carbon monoxide. Carbon dioxide (CO<sub>2</sub>). Sulfur oxides. Phosphorus oxides. Nitrogen oxides (NO<sub>x</sub>). Carbon black

**5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus.

**Additional information**

Extinguishing materials should be selected according to the surrounding area. Use water spray/stream to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately. Do not empty into drains or the aquatic environment.

## SECTION 6: Accidental release measures

**6.1. Personal precautions, protective equipment and emergency procedures**

High slip hazard because of leaking or spilled product. Remove all sources of ignition. Wear respiratory protection when in the presence of vapour, dust, and aerosols. Avoid contact with skin, eye and clothing.

**6.2. Environmental precautions**

Do not empty into drains or the aquatic environment. In case of gas being released or leakage into waters, ground or the drainage system, the appropriate authorities must be informed. Prevent spreading over great surfaces (e.g. by damming or installing oil booms).

**6.3. Methods and material for containment and cleaning up**

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the assimilated material according to the section on waste disposal. Clean contaminated objects and areas thoroughly observing environmental regulations.

**6.4. Reference to other sections**

Refer to the provisions listed in Sections 8, 12 and 13.

## SECTION 7: Handling and storage

**7.1. Precautions for safe handling****Advice on safe handling**

Work in well ventilated zones or use proper respiratory protection. Avoid oil mist. In case of open handling equipment with built-in suction must be used. Avoid contact with skin, eye and clothing.

**Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking.

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Keep the packing dry and well sealed to prevent contamination and absorption of dampness. Keep container tightly closed in a cool place.

**Advice on storage compatibility**

Keep away from food, drink and animal feedingstuffs.  
Keep away from: Oxidizing agents.

**Further information on storage conditions**

Recommended storage temperature: 10 - 30°C  
Protect against: heat. UV-radiation/sunlight. frost.

**7.3. Specific end use(s)**

Further information: refer to Technical Data Sheet.



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### ADDINOL Gear Oil CKT 150

Print date: 09.02.2015

Product code: 741096

Page 4 of 8

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Additional advice on limit values

Recommended limit value for oil mist

TWA: 5 mg/m<sup>3</sup>STEL: 10 mg/m<sup>3</sup>

The product does not contain any relevant quantities of substances with legally established exposure limitation.

### 8.2. Exposure controls



#### Appropriate engineering controls

Provide for sufficient ventilation and punctiform suction at critical points.

#### Protective and hygiene measures

Wash hands before breaks and at the end of work. Take off immediately all contaminated clothing.

Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

#### Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): DIN EN 166

#### Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): DIN EN 374

Duration of wearing with permanent contact: 480 min

Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.7 mm.

Duration of wearing with occasional contact (splashes): 30 min

Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.4 mm

Protect skin by using skin protective cream.

#### Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

#### Respiratory protection

If technical suction or ventilation measures are not possible or are insufficient, protective breathing apparatus must be worn. Breathing protection with filter against organic gases and vapours type A - boiling point > 65°C: A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	liquid
Colour:	yellow
Odour:	characteristic

#### Test method

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**ADDINOL Gear Oil CKT 150**

Print date: 09.02.2015

Product code: 741096

Page 5 of 8

**Changes in the physical state**

Initial boiling point and boiling range:	not determined
Flash point:	250 °C DIN EN ISO 2592
Ignition temperature:	not determined
Density (at 15 °C):	0,848 g/cm <sup>3</sup> DIN 51757
Water solubility:	virtually insoluble
Viscosity / kinematic: (at 40 °C)	155 mm <sup>2</sup> /s ASTM D 7042

**SECTION 10: Stability and reactivity****10.1. Reactivity**

Stable with proper care and handling.

**10.2. Chemical stability**

The product is chemically stable when handled and stored under normal conditions.

**10.3. Possibility of hazardous reactions**

No decomposition if used as intended.

**10.4. Conditions to avoid**

Refer to chapter 7 No further action is necessary.

Do not overheat to avoid decomposition by heat.

**10.5. Incompatible materials**

Reacts with : Oxidizing agents, strong.

**10.6. Hazardous decomposition products**Can be released in case of fire: Carbon monoxide. Carbon dioxide (CO<sub>2</sub>). Sulfur oxides. Phosphorus oxides. Nitrogen oxides (NO<sub>x</sub>). Carbon black**SECTION 11: Toxicological information****11.1. Information on toxicological effects****Acute toxicity**

No data available

Mixture not tested.

CAS No	Chemical name				
	Exposure routes	Method	Dose	Species	Source
n.a.	Long-chained alkyl amine				
	oral	ATE	500 mg/kg		
	dermal	ATE	300 mg/kg		
	inhalative vapour	ATE	0,5 mg/l		
	inhalative aerosol	ATE	0,05 mg/l		

**Irritation and corrosivity**

Irritant effect on the eye: mild irritant.

Irritant effect on the skin: Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

**Sensitising effects**

Contains: &lt; 0,15% Long-chained alkyl amine. May produce an allergic reaction.

**Severe effects after repeated or prolonged exposure**

Prolonged/repetitive skin contact may cause skin defatting or dermatitis.



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### ADDINOL Gear Oil CKT 150

Print date: 09.02.2015

Product code: 741096

Page 6 of 8

**Carcinogenic/mutagenic/toxic effects for reproduction**

No data available

**Specific effects in experiment on an animal**

No data available

## SECTION 12: Ecological information

**12.1. Toxicity**

No data available

Mixture not tested.

**12.2. Persistence and degradability**

Not easily bio-degradable (according to OECD-criteria). Do not empty into drains or the aquatic environment.

**12.3. Bioaccumulative potential**

No data available

**12.4. Mobility in soil**

Due to its low solubility in water the product is almost completely mechanically separated in biological waste water treatment plants.

**12.5. Results of PBT and vPvB assessment**

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

**12.6. Other adverse effects**

No data available

**Further information**

Do not allow uncontrolled leakage of product into the environment.

## SECTION 13: Disposal considerations

**13.1. Waste treatment methods****Advice on disposal**

Must not be disposed of with domestic refuse. Do not empty into drains or the aquatic environment.

**Waste disposal number of waste from residues/unused products**

130206 OIL WASTES AND WASTES OF LIQUID FUELS (except edible oils, and those in chapters 05, 12 and 19); waste engine, gear and lubricating oils; synthetic engine, gear and lubricating oils  
Classified as hazardous waste.

**Contaminated packaging**

Contaminated packing must be completely emptied and can be re-used following appropriate cleaning.  
Packing which cannot be properly cleaned must be thrown away. Waste disposal according to official state regulations.

## SECTION 14: Transport information

**Land transport (ADR/RID)****14.1. UN number:** -**Inland waterways transport (ADN)****14.1. UN number:** -**Marine transport (IMDG)****14.1. UN number:** -**Air transport (ICAO)****14.1. UN number:** -



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### ADDINOL Gear Oil CKT 150

Print date: 09.02.2015

Product code: 741096

Page 7 of 8

#### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

#### 14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

#### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

not applicable

#### Other applicable information

Not a hazardous material with respect to these transportation regulations.

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### National regulatory information

Water contaminating class (D): 1 - slightly water contaminating

#### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

### SECTION 16: Other information

#### Full text of R phrases referred to under Sections 2 and 3

22	Harmful if swallowed.
23/24	Toxic by inhalation and in contact with skin.
34	Causes burns.
38	Irritating to skin.
41	Risk of serious damage to eyes.
43	May cause sensitisation by skin contact.
48/23	Toxic: danger of serious damage to health by prolonged exposure through inhalation.
50	Very toxic to aquatic organisms.
51	Toxic to aquatic organisms.
53	May cause long-term adverse effects in the aquatic environment.

#### Full text of H statements referred to under Sections 2 and 3

H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

#### Further Information

This mixture is classified as not hazardous according to Regulation (EC) 1272/2008 [GHS].

These given data only refer to the named product. If the product is used together with other materials or in manufacturing processes the data might not be applicable any more. The data are based on today's state of our knowledge and experience. They are, however, no guarantee of any specific product properties and do not established any legally valid contractual relationship.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### ADDINOL Gear Oil CKT 150

Print date: 09.02.2015

Product code: 741096

Page 8 of 8

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*