



Safety Data Sheet

according to Regulation (EC) No 1907/2006

ADDINOL Super Power MV 0537

Print date: 05.03.2015

Product code: 720992

Page 1 of 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

ADDINOL Super Power MV 0537

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Motor oil.

1.3. Details of the supplier of the safety data sheet

| | | |
|-------------------------|--------------------------------|-------------------------------|
| Company name: | ADDINOL Lube Oil GmbH | |
| | Gebäude 4609 | |
| Street: | Am Haupttor | |
| Place: | D-06237 Leuna | |
| Telephone: | +49 (0) 3461 845-201 | Telefax: +49 (0) 3461 845-561 |
| e-mail: | info@addinol.de | |
| Contact person: | Application Technology | |
| Internet: | www.addinol.de | |
| Responsible Department: | ADDINOL Application Technology | |

1.4. Emergency telephone number:

+49 (0) 3461 845-201 - This number is serviced during office hours.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

R phrases:
Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

GHS classification

Hazard categories:
Hazardous to the aquatic environment: Aquatic Chronic 3
Hazard Statements:
Harmful to aquatic life with long lasting effects.

2.2. Label elements

Hazard statements

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P273 Avoid release to the environment.
P501

Additional advice on labelling

This preparation is hazardous in the sense of regulation (EC) No 1272/2008 [GHS].

The preparation is dangerous in the sense of Directive 1999/45/EC.

2.3. Other hazards

Spilled product must not leak into the ground.
Do not allow uncontrolled leakage of product into the environment.
Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

ADDINOL Super Power MV 0537

Print date: 05.03.2015

Product code: 720992

Page 2 of 8

Hazardous components

| EC No | Chemical name | Quantity |
|------------------|--|----------|
| CAS No | Classification | |
| Index No | GHS classification | |
| REACH No | | |
| 253-249-4 | Bis(nonylphenyl)amine | < 1,30 % |
| 36878-20-3 | R53 | |
| | Aquatic Chronic 4; H413 | |
| 01-2119488911-28 | | |
| 283-392-8 | Phosphorodithioic acid, mixed O,O-bis (1,3-dimethylbutyl and iso-Pr)esters, zinc salts | < 0,95 % |
| 84605-29-8 | Xi - Irritant, N - Dangerous for the environment R38-41-51-53 | |
| | Skin Irrit. 2, Eye Dam. 1, Aquatic Chronic 2; H315 H318 H411 | |
| 01-2119493626-26 | | |
| 310-154-3 | Phenol, dodecyl-, branched | < 0,15 % |
| 121158-58-5 | Xn - Harmful, N - Dangerous for the environment R62-36/38-50-53 | |
| | Skin Irrit. 2, Eye Irrit. 2, Repr. 2, Aquatic Acute 1, Aquatic Chronic 1; H315 H319 H361 H400 H410 | |
| 01-2119513207-49 | | |
| 204-539-4 | Diphenyl amine | < 0,15 % |
| 122-39-4 | T - Toxic, N - Dangerous for the environment R23/24/25-33-50-53 | |
| | Acute Tox. 3, Acute Tox. 3, Acute Tox. 3, STOT RE 2, Aquatic Acute 1, Aquatic Chronic 1; H301 H311 H331 H373 H400 H410 | |
| 204-884-0 | 2,6-di-tert-butylphenol | < 0,15 % |
| 128-39-2 | Xi - Irritant, N - Dangerous for the environment R38-50-53 | |
| | Skin Irrit. 2, Aquatic Acute 1, Aquatic Chronic 1; H315 H400 H410 | |
| 01-2119490822-33 | | |

Full text of R and H phrases: see Section 16.

Further Information

DMSO-Extrakt < 3 %, IP 346.

Concentration of PCBs < 1mg/kg.

Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

Self-protection of the first aider.. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

After inhalation

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. In case of skin irritation, seek medical treatment.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

ADDINOL Super Power MV 0537

Print date: 05.03.2015

Product code: 720992

Page 3 of 8

After ingestion

Do not induce vomiting.

Rinse mouth thoroughly with water. Immediately get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam. Extinguishing powder. Carbon dioxide (CO₂). Atomized water.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Can be released in case of fire: Carbon monoxide. Carbon dioxide (CO₂). aldehydes. Nitrogen oxides (NO_x). Sulfur oxides. Hydrogen sulphide (H₂S). Carbon black.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Extinguishing materials should be selected according to the surrounding area. Use water spray/stream to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately. Do not empty into drains or the aquatic environment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

High slip hazard because of leaking or spilled product. Remove all sources of ignition. Wear respiratory protection when in the presence of vapour, dust, and aerosols. Avoid contact with skin, eye and clothing.

6.2. Environmental precautions

Do not empty into drains or the aquatic environment. In case of gas being released or leakage into waters, ground or the drainage system, the appropriate authorities must be informed. Prevent spreading over great surfaces (e.g. by damming or installing oil booms).

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the assimilated material according to the section on waste disposal. Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Refer to the provisions listed in Sections 8, 12 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Work in well ventilated zones or use proper respiratory protection. Avoid oil mist. In case of open handling equipment with built-in suction must be used. Avoid contact with skin, eye and clothing.

Advice on protection against fire and explosion

Remove all sources of ignition.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

ADDINOL Super Power MV 0537

Print date: 05.03.2015

Product code: 720992

Page 4 of 8

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep the packing dry and well sealed to prevent contamination and absorption of dampness. Keep container tightly closed in a cool place.

Advice on storage compatibility

Keep away from food, drink and animal feedingstuffs.

Keep away from: Oxidizing agents.

Further information on storage conditions

Recommended storage temperature: 10 - 30°C

Protect against: heat. UV-radiation/sunlight. frost.

7.3. Specific end use(s)

Motor oil. Further information: refer to Technical Data Sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

| CAS No | Substance | ppm | mg/m ³ | fib/cm ³ | Category | Origin |
|----------|---------------|-----|-------------------|---------------------|---------------|--------|
| 122-39-4 | Diphenylamine | - | 10 | | TWA (8 h) | |
| | | - | 20 | | STEL (15 min) | |

Additional advice on limit values

Recommended limit value for oil mist

TWA: 5 mg/m³

STEL: 10 mg/m³

The product does not contain any relevant quantities of substances with legally established exposure limitation.

8.2. Exposure controls



Appropriate engineering controls

Provide for sufficient ventilation and punctiform suction at critical points.

Protective and hygiene measures

Wash hands before breaks and at the end of work. Take off immediately all contaminated clothing.

Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): DIN EN 166

Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): DIN EN 374

Duration of wearing with permanent contact: 480 min

Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.7 mm.

Duration of wearing with occasional contact (splashes): 30 min



Safety Data Sheet

according to Regulation (EC) No 1907/2006

ADDINOL Super Power MV 0537

Print date: 05.03.2015

Product code: 720992

Page 5 of 8

Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.4 mm

Protect skin by using skin protective cream.

Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

Respiratory protection

If technical suction or ventilation measures are not possible or are insufficient, protective breathing apparatus must be worn.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|-----------------|--------------------|
| Physical state: | liquid |
| Colour: | yellow - brown |
| Odour: | like: mineral oil. |

Test method

Changes in the physical state

| | |
|--|-------------------------------------|
| Initial boiling point and boiling range: | not determined |
| Flash point: | > 230 °C DIN EN ISO 2592 |
| Ignition temperature: | not determined |
| Density (at 15 °C): | 0,855 g/cm ³ DIN 51757 |
| Water solubility: | virtually insoluble |
| Viscosity / kinematic: (at 100 °C) | 11,7 mm ² /s ASTM D 7042 |

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable with proper care and handling.

10.2. Chemical stability

The product is chemically stable when handled and stored under normal conditions.

10.3. Possibility of hazardous reactions

No decomposition if used as intended.

10.4. Conditions to avoid

Refer to chapter 7 No further action is necessary.

Do not overheat to avoid decomposition by heat.

10.5. Incompatible materials

Reacts with :Oxidizing agents, strong. Acid.

10.6. Hazardous decomposition products

Can be released in case of fire: Carbon monoxide. Carbon dioxide (CO₂). aldehydes. Nitrogen oxides (NO_x). Sulfur oxides. Hydrogen sulphide (H₂S). Carbon black.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

ADDINOL Super Power MV 0537

Print date: 05.03.2015

Product code: 720992

Page 6 of 8

No data available

Mixture not tested.

| CAS No | Chemical name | | | | |
|----------|--------------------|--------|-----------|---------|--------|
| | Exposure routes | Method | Dose | Species | Source |
| 122-39-4 | Diphenyl amine | | | | |
| | oral | ATE | 100 mg/kg | | |
| | dermal | ATE | 300 mg/kg | | |
| | inhalative vapour | ATE | 3 mg/l | | |
| | inhalative aerosol | ATE | 0,5 mg/l | | |

Irritation and corrosivity

Irritant effect on the eye: mild irritant.

Irritant effect on the skin: Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

Sensitising effects

Evaluation: no danger of sensitization.

Severe effects after repeated or prolonged exposure

Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

Carcinogenic/mutagenic/toxic effects for reproduction

No data available

Specific effects in experiment on an animal

No data available

SECTION 12: Ecological information**12.1. Toxicity**

No data available

Mixture not tested.

12.2. Persistence and degradability

Not easily bio-degradable (according to OECD-criteria). Do not empty into drains or the aquatic environment.

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

Due to its low solubility in water the product is almost completely mechanically separated in biological waste water treatment plants.

12.5. Results of PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

12.6. Other adverse effects

No data available

Further information

Do not allow uncontrolled leakage of product into the environment.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Advice on disposal**

Must not be disposed of with domestic refuse. Do not empty into drains or the aquatic environment.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

ADDINOL Super Power MV 0537

Print date: 05.03.2015

Product code: 720992

Page 7 of 8

Waste disposal number of waste from residues/unused products

- 130206 OIL WASTES AND WASTES OF LIQUID FUELS (except edible oils, and those in chapters 05, 12 and 19); waste engine, gear and lubricating oils; synthetic engine, gear and lubricating oils
Classified as hazardous waste.

Contaminated packaging

Contaminated packing must be completely emptied and can be re-used following appropriate cleaning.
Waste disposal according to official state regulations. Packing which cannot be properly cleaned must be thrown away.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: -

Inland waterways transport (ADN)

14.1. UN number: -

Marine transport (IMDG)

14.1. UN number: -

Air transport (ICAO)

14.1. UN number: -

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

not applicable

Other applicable information

Not a hazardous material with respect to these transportation regulations.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulatory information

Water contaminating class (D): 2 - water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Full text of R phrases referred to under Sections 2 and 3

- | | |
|----------|---|
| 23/24/25 | Toxic by inhalation, in contact with skin and if swallowed. |
| 33 | Danger of cumulative effects. |
| 36/38 | Irritating to eyes and skin. |
| 38 | Irritating to skin. |
| 41 | Risk of serious damage to eyes. |
| 50 | Very toxic to aquatic organisms. |
| 51 | Toxic to aquatic organisms. |
| 52/53 | Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. |
| 53 | May cause long-term adverse effects in the aquatic environment. |
| 62 | Possible risk of impaired fertility. |

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

ADDINOL Super Power MV 0537

Print date: 05.03.2015

Product code: 720992

Page 8 of 8

Full text of H statements referred to under Sections 2 and 3

| | |
|------|--|
| H301 | Toxic if swallowed. |
| H311 | Toxic in contact with skin. |
| H315 | Causes skin irritation. |
| H318 | Causes serious eye damage. |
| H319 | Causes serious eye irritation. |
| H331 | Toxic if inhaled. |
| H361 | Suspected of damaging fertility or the unborn child. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |
| H400 | Very toxic to aquatic life. |
| H410 | Very toxic to aquatic life with long lasting effects. |
| H411 | Toxic to aquatic life with long lasting effects. |
| H412 | Harmful to aquatic life with long lasting effects. |
| H413 | May cause long lasting harmful effects to aquatic life. |

Further Information

This preparation is hazardous in the sense of regulation (EC) No 1272/2008 [GHS].

These given data only refer to the named product. If the product is used together with other materials or in manufacturing processes the data might not be applicable any more. The data are based on today's state of our knowledge and experience. They are, however, no guarantee of any specific product properties and do not established any legally valid contractual relationship.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)