



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### ADDINOL Compressor Oil VDL 46 S

Print date: 30.03.2015

Product code: 754021

Page 1 of 7

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

ADDINOL Compressor Oil VDL 46 S

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

###### Use of the substance/mixture

Lubricant and additive.

##### 1.3. Details of the supplier of the safety data sheet

Company name:	ADDINOL Lube Oil GmbH	
	Gebäude 4609	
Street:	Am Haupttor	
Place:	D-06237 Leuna	
Telephone:	+49 (0) 3461 845-201	Telefax: +49 (0) 3461 845-561
e-mail:	info@addinol.de	
Contact person:	Application Technology	
Internet:	www.addinol.de	
Responsible Department:	ADDINOL Application Technology	

**1.4. Emergency telephone number:** +49 (0) 3461 845-201 - This number is serviced during office hours.

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

###### Classification according to Directive 67/548/EEC or 1999/45/EC

R phrases:

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

###### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Hazard categories:

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Harmful to aquatic life with long lasting effects.

##### 2.2. Label elements

###### Hazard statements

H412 Harmful to aquatic life with long lasting effects.

###### Precautionary statements

P273 Avoid release to the environment.

P501 Dispose of contents/container to a waste disposal system.

###### Additional advice on labelling

This preparation is hazardous in the sense of regulation (EC) No 1272/2008 [GHS].

##### 2.3. Other hazards

Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

Process vapors can irritate airways, skin and eyes.

Do not allow uncontrolled leakage of product into the environment.

#### SECTION 3: Composition/information on ingredients

##### 3.2. Mixtures

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**ADDINOL Compressor Oil VDL 46 S**

Print date: 30.03.2015

Product code: 754021

Page 2 of 7

**Hazardous components**

EC No	Chemical name	Quantity
CAS No	Classification according to Directive 67/548/EEC	
Index No	Classification according to Regulation (EC) No. 1272/2008 [CLP]	
REACH No		
204-884-0	2,6-di-tert-butylphenol	
128-39-2	Xi - Irritant, N - Dangerous for the environment R38-50-53	< 0,30 %
	Skin Irrit. 2, Aquatic Acute 1 (M-Factor = 1), Aquatic Chronic 1 (M-Factor = 1); H315 H400 H410	
01-2119490822-33		

Full text of R-, H- and EUH-phrases: see section 16.

**Further Information**

DMSO-Extrakt &lt; 3 %, IP 346.

Concentration of PCBs &lt; 1mg/kg.

Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

**SECTION 4: First aid measures****4.1. Description of first aid measures****General information**

Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

**After inhalation**

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist.

**After contact with skin**

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. In case of skin irritation, seek medical treatment.

**After contact with eyes**

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

**After ingestion**

Do NOT induce vomiting.

Rinse mouth thoroughly with water. Call a physician immediately.

**4.2. Most important symptoms and effects, both acute and delayed**

No information available.

**4.3. Indication of any immediate medical attention and special treatment needed**

First Aid, decontamination, treatment of symptoms.

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**Foam. Extinguishing powder. Carbon dioxide (CO<sub>2</sub>). Atomized water.**Unsuitable extinguishing media**

High power water jet.



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### ADDINOL Compressor Oil VDL 46 S

Print date: 30.03.2015

Product code: 754021

Page 3 of 7

#### **5.2. Special hazards arising from the substance or mixture**

In case of fire may be liberated: Carbon monoxide. Carbon dioxide (CO<sub>2</sub>). Sulfur oxides. Phosphorus oxides. Nitrogen oxides (NO<sub>x</sub>). carbon black.

#### **5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus.

#### **Additional information**

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray jet to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately.

### **SECTION 6: Accidental release measures**

#### **6.1. Personal precautions, protective equipment and emergency procedures**

High slip hazard because of leaking or spilled product. Remove all sources of ignition. Wear breathing apparatus if exposed to vapours/dusts/aerosols. Avoid contact with skin, eye and clothing.

#### **6.2. Environmental precautions**

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Prevent spread over a wide area (e.g. by containment or oil barriers).

#### **6.3. Methods and material for containment and cleaning up**

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean contaminated objects and areas thoroughly observing environmental regulations.

#### **6.4. Reference to other sections**

Refer to the provisions listed in Sections 8, 12 and 13.

### **SECTION 7: Handling and storage**

#### **7.1. Precautions for safe handling**

##### **Advice on safe handling**

Work in well-ventilated zones or use proper respiratory protection. Avoid oil mist. If handled uncovered, arrangements with local exhaust ventilation have to be used. Avoid contact with skin, eye and clothing.

##### **Advice on protection against fire and explosion**

Keep away from sources of ignition. - No smoking.

#### **7.2. Conditions for safe storage, including any incompatibilities**

##### **Requirements for storage rooms and vessels**

Keep the packing dry and well sealed to prevent contamination and absorption of humidity. Keep container tightly closed in a cool place.

##### **Advice on storage compatibility**

Keep away from food, drink and animal feedingstuffs.  
Keep away from: Oxidizing agents.

##### **Further information on storage conditions**

Recommended storage temperature: 10 - 30°C  
Protect against: heat. UV-radiation/sunlight. frost.

#### **7.3. Specific end use(s)**

Further information: see technical data sheet.

### **SECTION 8: Exposure controls/personal protection**

#### **8.1. Control parameters**

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### ADDINOL Compressor Oil VDL 46 S

Print date: 30.03.2015

Product code: 754021

Page 4 of 7

#### Additional advice on limit values

Recommended limit value for oil mist

TWA: 5 mg/m<sup>3</sup>

STEL: 10 mg/m<sup>3</sup>

The product does not contain any relevant quantities of substances with legally established exposure limitation.

#### 8.2. Exposure controls



#### Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

#### Protective and hygiene measures

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

#### Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): DIN EN 166

#### Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): DIN EN 374

Duration of wearing with permanent contact: 480 min

Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.7 mm.

Wearing time with occasional contact (splashes): 30 min

Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.4 mm

Protect skin by using skin protective cream.

#### Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

#### Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Breathing protection with filter against organic gases and vapours type A - boiling point > 65°C: A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state:	liquid
Colour:	yellow
Odour:	like: mineral oil.

#### Test method

#### Changes in the physical state

Initial boiling point and boiling range:

not determined

Flash point:

260 °C DIN EN ISO 2592



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### ADDINOL Compressor Oil VDL 46 S

Print date: 30.03.2015

Product code: 754021

Page 5 of 7

Ignition temperature:	not determined
Density (at 15 °C):	0,838 g/cm <sup>3</sup> DIN 51757
Water solubility:	virtually insoluble
Viscosity / kinematic: (at 40 °C)	45 mm <sup>2</sup> /s ASTM D 7042

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Stable with proper care and handling.

### 10.2. Chemical stability

The product is chemically stable when handled and stored under normal conditions.

### 10.3. Possibility of hazardous reactions

No decomposition if used as intended.

### 10.4. Conditions to avoid

Refer to chapter 7 No further action is necessary.

Do not overheat to avoid decomposition by heat.

### 10.5. Incompatible materials

Reacts with : Oxidizing agents, strong. Acid.

### 10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon monoxide. Carbon dioxide (CO<sub>2</sub>). Sulfur oxides. Phosphorus oxides. Nitrogen oxides (NO<sub>x</sub>). carbon black.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Acute toxicity

No data available

Mixture not tested.

#### Irritation and corrosivity

Irritant effect on the eye: mild irritant.

Irritant effect on the skin: Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

#### Sensitising effects

Evaluation: no danger of sensitization.

#### Severe effects after repeated or prolonged exposure

Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

#### Carcinogenic/mutagenic/toxic effects for reproduction

No data available

#### Specific effects in experiment on an animal

No data available

## SECTION 12: Ecological information

### 12.1. Toxicity

No data available

Mixture not tested.

### 12.2. Persistence and degradability

Not easily bio-degradable (according to OECD-criteria). Do not allow to enter into surface water or



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### ADDINOL Compressor Oil VDL 46 S

Print date: 30.03.2015

Product code: 754021

Page 6 of 7

drains.

#### **12.3. Bioaccumulative potential**

No data available

#### **12.4. Mobility in soil**

Due to its low solubility in water the product is almost completely mechanically separated in biological waste water treatment plants.

#### **12.5. Results of PBT and vPvB assessment**

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

#### **12.6. Other adverse effects**

No data available

#### **Further information**

Do not allow uncontrolled leakage of product into the environment.

### SECTION 13: Disposal considerations

#### **13.1. Waste treatment methods**

##### **Advice on disposal**

Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

##### **Waste disposal number of waste from residues/unused products**

130206 OIL WASTES AND WASTES OF LIQUID FUELS (except edible oils, and those in chapters 05, 12 and 19); waste engine, gear and lubricating oils; synthetic engine, gear and lubricating oils  
Classified as hazardous waste.

##### **Contaminated packaging**

Contaminated packages must be completely emptied and can be re-used following proper cleaning.  
Dispose of waste according to applicable legislation. Packing which cannot be properly cleaned must be thrown away.

### SECTION 14: Transport information

#### **Land transport (ADR/RID)**

**14.1. UN number:** -

#### **Inland waterways transport (ADN)**

**14.1. UN number:** -

#### **Marine transport (IMDG)**

**14.1. UN number:** -

#### **Air transport (ICAO)**

**14.1. UN number:** -

#### **14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: no

#### **14.6. Special precautions for user**

Unless specified otherwise, general measures for safe transport must be followed.

#### **14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

not applicable

#### **Other applicable information**

No dangerous good in sense of these transport regulations.

### SECTION 15: Regulatory information

#### **15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### ADDINOL Compressor Oil VDL 46 S

Print date: 30.03.2015

Product code: 754021

Page 7 of 7

#### National regulatory information

Water contaminating class (D): 1 - slightly water contaminating

#### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

### SECTION 16: Other information

#### Relevant R-phrases (Number and full text)

- 38 Irritating to skin.
- 50 Very toxic to aquatic organisms.
- 53 May cause long-term adverse effects in the aquatic environment.

#### Relevant H- and EUH-phrases (Number and full text)

- H315 Causes skin irritation.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.

#### Further Information

This preparation is hazardous in the sense of regulation (EC) No 1272/2008 [GHS].

These given data only refer to the named product. If the product is used together with other materials or in manufacturing processes the data might not be applicable any more. The data are based on today's state of our knowledge and experience. They are, however, no guarantee of any specific product properties and do not established any legally valid contractual relationship.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*