



according to Regulation (EC) No 1907/2006

# **ADDINOL Chain Lube XHT 250**

Print date: 04.03.2014

Product code: 76602554

Page 1 of 7

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

# 1.1. Product identifier

ADDINOL Chain Lube XHT 250

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

# Use of the substance/mixture

Lubricant and additive.

# 1.3. Details of the supplier of the safety data sheet

1.4. Emergency telephone	+49 (0) 3461 845-201 - This number i	is serviced during office hours.
Responsible Department:	ADDINOL Application Technology	
Internet:	www.addinol.de	
Contact person:	Application Technology	
e-mail:	info@addinol.de	
Telephone:	+49 (0) 3461 845-201	Telefax: +49 (0) 3461 845-561
Place:	D-06237 Leuna	
Street:	Am Haupttor	
	Gebäude 4609	
Company name:	ADDINOL Lube Oil GmbH	

#### <u>number:</u>

# **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

This preparation is hazardous in the sense of regulation (EC) No 1272/2008 [GHS].

## **GHS classification**

Hazard categories: Hazardous to the aquatic environment: Aquatic Chronic 3 Hazard Statements: Harmful to aquatic life with long lasting effects.

### 2.2. Label elements

### Hazard statements

H412

P501

Harmful to aquatic life with long lasting effects.

#### Precautionary statements P273

Avoid release to the environment.

Dispose of contents/container to a waste disposal system.

# Additional advice on labelling

There is no requirement for the product to be specially labelled according to EC directives or the corresponding national laws.

# 2.3. Other hazards

Prolonged/repetitive skin contact may cause skin defattening or dermatitis. Spilled product must not leak into the ground. Do not allow uncontrolled leakage of product into the environment.

# **SECTION 3: Composition/information on ingredients**

# 3.2. Mixtures



according to Regulation (EC) No 1907/2006

**ADDINOL Chain Lube XHT 250** 

Print date: 04.03.2014

Product code: 76602554

Page 2 of 7

#### Hazardous components

EC No	Chemical name	Quantity
CAS No	Classification	
Index No	GHS classification	
REACH No		
253-138-0	Trimellitat Ester	< 65 %
	R53	
	Aquatic Chronic 4; H413	
500-183-1	1-Decene homopolymer, hydrogenated	< 30 %
68037-01-4		
	Asp. Tox. 1; H304	
01-2119486452-34		
273-066-3	Triaryl phosphate isopropylated	< 1,75 %
68937-41-7	N - Dangerous for the environment R51-53	
	Aquatic Chronic 2; H411	
204-112-2	Triphenyl phosphate	< 1,25 %
115-86-6	N - Dangerous for the environment R50-53	
	Aquatic Acute 1, Aquatic Chronic 1; H400 H410	
233-593-1	4,4'-Methylene bis(dibutyldithiocarbamate)	0,50 %
10254-57-6	R52-53	
	Aquatic Chronic 4; H413	

Full text of R and H phrases: see Section 16.

## Further Information

DMSO-Extrakt < 3 %, IP 346.

Concentration of PCBs < 1mg/kg.

Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

# **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

#### General information

Self-protection of the first aider.. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

## After inhalation

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist.

#### After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. In case of skin irritation, seek medical treatment.

## After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

## After ingestion

Do not induce vomiting. Rinse mouth immediately and drink large quantities of water. Immediately get medical attention.



according to Regulation (EC) No 1907/2006

# **ADDINOL Chain Lube XHT 250**

Print date: 04.03.2014

Product code: 76602554

Page 3 of 7

#### **SECTION 5: Firefighting measures**

# 5.1. Extinguishing media

### Suitable extinguishing media

Foam. Extinguishing powder. Carbon dioxide (CO2). Atomized water.

# Extinguishing media which must not be used for safety reasons

High power water jet.

## 5.2. Special hazards arising from the substance or mixture

Can be released in case of fire: Carbon monoxide. Carbon dioxide (CO2). Sulfur oxides. Phosphorus oxides. Nitrogen oxides (NOx). Carbon black

# 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

#### Additional information

Extinguishing materials should be selected according to the surrounding area. Use water spray/stream to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

High slip hazard because of leaking or spilled product. The following must be prevented: skin contact. Eye contact. inhalation. Wear respiratory protection when in the presence of vapour, dust, and aerosols.

#### 6.2. Environmental precautions

Do not empty into drains or the aquatic environment. In case of gas being released or leakage into waters, ground or the drainage system, the appropriate authorities must be informed. Prevent spreading over great surfaces (e.g. by damming or installing oil booms).

# 6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the assimilated material according to the section on waste disposal. Clean contaminated objects and areas thoroughly observing environmental regulations.

# **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

#### Advice on safe handling

Work in well ventilated zones or use proper respiratory protection. Avoid oil mist In case of open handling equipment with built-in suction must be used. Avoid contact with skin, eye and clothing.

#### Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

## 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep the packing dry and well sealed to prevent contamination and absorbtion of dampness.

#### Advice on storage compatibility

Keep away from food, drink and animal feedingstuffs.

Keep away from: Oxidizing agents.

#### Further information on storage conditions

Recommended storage temperature: 10 - 30°C Protect against: heat. UV-radiation/sunlight.

#### **SECTION 8: Exposure controls/personal protection**



according to Regulation (EC) No 1907/2006

## **ADDINOL Chain Lube XHT 250**

Print date: 04.03.2014

Product code: 76602554

Page 4 of 7

# 8.1. Control parameters

## **Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
115-86-6	Triphenyl phosphate	-	3		TWA (8 h)	WEL
		-	6		STEL (15 min)	WEL

# Additional advice on limit values

Recommended limit value for oil mist TWA: 5 mg/m<sup>3</sup>

STEL: 10 mg/m<sup>3</sup>

The product does not contain any relevant quantities of substances with legally established exposure limitation.

# 8.2. Exposure controls



#### **Occupational exposure controls**

Provide for sufficient ventilation and punctiform suction at critical points.

## Protective and hygiene measures

Wash hands before breaks and at the end of work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

#### **Respiratory protection**

If technical suction or ventilation measures are not possible or are insufficient, protective breathing apparatus must be worn. Breathing protection with filter against organic gases and vapours type A boiling point > 65°C: A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

## Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): DIN EN 374

Duration of wearing with permanent contact: 480 min Suitable material: NBR (Nitrile rubber). Thickness of glove material: 0.7 mm.

Duration of wearing with occasional contact (splashes): 30 min Suitable material: NBR (Nitrile rubber). Thickness of glove material: 0.4 mm

Protect skin by using skin protective cream.

# Eye protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): DIN EN 166

# Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.





according to Regulation (EC) No 1907/2006

# **ADDINOL Chain Lube XHT 250**

Print date: 04.03.2014

Product code: 76602554

Page 5 of 7

# **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Physical state:liquidColour:yellow - brownOdour:characteristic

Test	method
------	--------

Changes in the physical state		
Boiling point:	> 200 °C	
Flash point:	282 °C	DIN ISO 2592
Ignition temperature:	> 400 °C	DIN 51794
Density (at 15 °C):	0,939 g/cm³	DIN 51757
Water solubility:	virtually insoluble	
Viscosity / kinematic: (at 40 °C)	250 mm²/s	DIN 51562

# **SECTION 10: Stability and reactivity**

### 10.4. Conditions to avoid

Refer to chapter 7 No further action is necessary. Do not overheat to avoid decomposition by heat.

### 10.5. Incompatible materials

Reacts with : Oxidizing agents, strong.

# 10.6. Hazardous decomposition products

Can be released in case of fire: Carbon monoxide. Carbon dioxide (CO2). Sulfur oxides. Phosphorus oxides. Nitrogen oxides (NOx). Carbon black

# **SECTION 11: Toxicological information**

## 11.1. Information on toxicological effects

#### Acute toxicity

Preparation related information:

Acute toxicity, oral, Rat. LD50: >2000 mg/kg

Test was carried out with a similar formulation.

#### Specific effects in experiment on an animal

No data available

## Irritation and corrosivity

Irritant effect on the eye: Not an irritant.

Irritant effect on the skin: Prolonged/repetitive skin contact may cause skin defattening or dermatitis.

#### Sensitising effects

Evaluation: no danger of sensitization.

### Severe effects after repeated or prolonged exposure

Prolonged/repetitive skin contact may cause skin defattening or dermatitis.

# Carcinogenic/mutagenic/toxic effects for reproduction

No data available

# **SECTION 12: Ecological information**



according to Regulation (EC) No 1907/2006

# **ADDINOL Chain Lube XHT 250**

Print date: 04.03.2014

Product code: 76602554

Page 6 of 7

## 12.1. Toxicity

No data available

Preparation not tested.

### 12.2. Persistence and degradability

Not easily bio-degradable (according to OECD-criteria). Do not empty into drains or the aquatic environment.

# 12.3. Bioaccumulative potential

No data available

#### 12.4. Mobility in soil

Due to its low solubility in water the product is almost completely mechanically separated in biological waste water treatment plants.

#### 12.5. Results of PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

#### 12.6. Other adverse effects

No data available

### **Further information**

Do not allow uncontrolled leakage of product into the environment.

# **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

#### Advice on disposal

Must not be disposed of with domestic refuse. Do not empty into drains or the aquatic environment.

#### Waste disposal number of waste from residues/unused products

130206 OIL WASTES AND WASTES OF LIQUID FUELS (except edible oils, and those in chapters 05, 12 and 19); waste engine, gear and lubricating oils; synthetic engine, gear and lubricating oils Classified as hazardous waste.

# Contaminated packaging

Contaminated packing must be completely emptied and can be re-used following appropriate cleaning. Packing which cannot be properly cleaned must be thrown away. Waste disposal according to official state regulations.

# **SECTION 14: Transport information**

Land transport (ADR/RID)		
<u>14.1. UN number:</u>	-	
Inland waterways transport (ADN)		
<u>14.1. UN number:</u>	-	
Marine transport (IMDG)		
<u>14.1. UN number:</u>	-	
Air transport (ICAO)		
<u>14.1. UN number:</u>	-	
14.5. Environmental hazards		
Dangerous for the environment:	no	

# Other applicable information

Not a hazardous material with respect to these transportation regulations.



according to Regulation (EC) No 1907/2006

## **ADDINOL Chain Lube XHT 250**

Print date: 04.03.2014

Product code: 76602554

Page 7 of 7

## **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## National regulatory information

Water contaminating class (D):

2 - water contaminating

### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

# **SECTION 16: Other information**

### Full text of R phrases referred to under Sections 2 and 3

- 50 Very toxic to aquatic organisms.
- 51 Toxic to aquatic organisms.
- 52 Harmful to aquatic organisms.
- 53 May cause long-term adverse effects in the aquatic environment.

## Full text of H statements referred to under Sections 2 and 3

- H304 May be fatal if swallowed and enters airways.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.
- H413 May cause long lasting harmful effects to aquatic life.

## **Further Information**

This preparation is hazardous in the sense of regulation (EC) No 1272/2008 [GHS].

These given data only refer to the named product. If the product is used together with other materials or in manufacturing processes the data might not be applicable any more. The data are based on today's state of our knowledge and experience. They are, however, no guarantee of any specific product properties and do not established any legally valid contructual relationship.

The receiver of our product is singulary responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)