



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### ADDINOL Gear Oil CLP 10

Print date: 07.05.2014

Product code: 741027

Page 1 of 7

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

ADDINOL Gear Oil CLP 10

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

###### Use of the substance/mixture

Gearbox oil.

##### 1.3. Details of the supplier of the safety data sheet

Company name:	ADDINOL Lube Oil GmbH	
	Gebäude 4609	
Street:	Am Haupttor	
Place:	D-06237 Leuna	
Telephone:	+49 (0) 3461 845-201	Telefax: +49 (0) 3461 845-561
e-mail:	info@addinol.de	
Contact person:	Application Technology	
Internet:	www.addinol.de	
Responsible Department:	ADDINOL Application Technology	

**1.4. Emergency telephone number:** +49 (0) 3461 845-201 - This number is serviced during office hours.

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

This preparation is hazardous in the sense of regulation (EC) No 1272/2008 [GHS].

###### GHS classification

Hazard categories:

Aspiration hazard: Asp. Tox. 1

Hazard Statements:

May be fatal if swallowed and enters airways.

##### 2.2. Label elements

Signal word:	Danger
Pictograms:	GHS08



###### Hazard statements

H304 May be fatal if swallowed and enters airways.

###### Precautionary statements

P102	Keep out of reach of children.
P103	Read label before use.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331	Do NOT induce vomiting.
P405	Store locked up.

##### 2.3. Other hazards

Process vapors can irritate airways, skin and eyes.  
Spilled product must not leak into the ground.  
Do not allow uncontrolled leakage of product into the environment.



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### ADDINOL Gear Oil CLP 10

Print date: 07.05.2014

Product code: 741027

Page 2 of 7

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### Hazardous components

EC No	Chemical name	Quantity
CAS No	Classification	
Index No	GHS classification	
REACH No		
265-158-7	Distillates (petroleum), hydrotreated light paraffinicBaseoil - unspecified	< 80 %
64742-55-8	Xn - Harmful R65	
	Asp. Tox. 1; H304	
265-077-7	Distillates (petroleum), heavy hydrocracked; Base oil unspecified	< 20 %
64741-76-0	Xn - Harmful R65	
	Asp. Tox. 1; H304	
01-2119486951-26		
224-235-5	Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate).	< 0,85 %
4259-15-8	Xi - Irritant, N - Dangerous for the environment R41-51-53	
	Eye Dam. 1, Aquatic Chronic 2; H318 H411	
01-2119493635-27		

Full text of R and H phrases: see Section 16.

#### Further Information

DMSO-Extrakt < 3 %, IP 346.

Concentration of PCBs < 1mg/kg.

Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

Self-protection of the first aider.. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

#### After inhalation

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist.

#### After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. Use skin protection ointment after cleaning. In case of skin irritation, seek medical treatment.

#### After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

#### After ingestion

Do not induce vomiting. Give activated carbon, in order to reduce the resorption in the gastro-enteric tract. Immediately get medical attention.

Caution if victim vomits: Risk of aspiration!

## SECTION 5: Firefighting measures



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### ADDINOL Gear Oil CLP 10

Print date: 07.05.2014

Product code: 741027

Page 3 of 7

#### **5.1. Extinguishing media**

##### **Suitable extinguishing media**

Foam. Extinguishing powder. Carbon dioxide (CO<sub>2</sub>). Atomized water.

##### **Unsuitable extinguishing media**

High power water jet.

#### **5.2. Special hazards arising from the substance or mixture**

Can be released in case of fire: Carbon monoxide. Carbon dioxide (CO<sub>2</sub>). Nitrogen oxides (NO<sub>x</sub>).  
Carbon black.

#### **5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus.

#### **Additional information**

Extinguishing materials should be selected according to the surrounding area. Use water spray/stream to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately.

### SECTION 6: Accidental release measures

#### **6.1. Personal precautions, protective equipment and emergency procedures**

High slip hazard because of leaking or spilled product. Keep away from sources of ignition - No smoking. Avoid oil mist Avoid contact with skin, eye and clothing.

#### **6.2. Environmental precautions**

Do not empty into drains or the aquatic environment. In case of gas being released or leakage into waters, ground or the drainage system, the appropriate authorities must be informed. Prevent spreading over great surfaces (e.g. by damming or installing oil booms).

#### **6.3. Methods and material for containment and cleaning up**

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the assimilated material according to the section on waste disposal. Clean contaminated objects and areas thoroughly observing environmental regulations.

### SECTION 7: Handling and storage

#### **7.1. Precautions for safe handling**

##### **Advice on safe handling**

Work in well ventilated zones or use proper respiratory protection. Avoid oil mist In case of open handling equipment with built-in suction must be used. Avoid contact with skin, eye and clothing.

##### **Advice on protection against fire and explosion**

When hot, product develops flammable vapours.

#### **7.2. Conditions for safe storage, including any incompatibilities**

##### **Requirements for storage rooms and vessels**

Keep the packing dry and well sealed to prevent contamination and absorption of dampness.

##### **Advice on storage compatibility**

Keep away from food, drink and animal feedingstuffs.  
Keep away from: Oxidizing agents.

##### **Further information on storage conditions**

Protect against: UV-radiation/sunlight.frost.  
Recommended storage temperature: 10 - 30°C

### SECTION 8: Exposure controls/personal protection

#### **8.1. Control parameters**



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### ADDINOL Gear Oil CLP 10

Print date: 07.05.2014

Product code: 741027

Page 4 of 7

#### Additional advice on limit values

Recommended limit value for oil mist

TWA: 5 mg/m<sup>3</sup>

STEL: 10 mg/m<sup>3</sup>

The product does not contain any relevant quantities of substances with legally established exposure limitation.

#### 8.2. Exposure controls



##### Appropriate engineering controls

Provide for sufficient ventilation and punctiform suction at critical points.

##### Protective and hygiene measures

Wash hands before breaks and at the end of work. Take off immediately all contaminated clothing.

Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

##### Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): DIN EN 166

##### Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): DIN EN 374

Duration of wearing with permanent contact: 480 min

Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.7 mm.

Duration of wearing with occasional contact (splashes): 30 min

Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.4 mm

Protect skin by using skin protective cream.

##### Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

##### Respiratory protection

If technical suction or ventilation measures are not possible or are insufficient, protective breathing apparatus must be worn.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	liquid
Colour:	yellow
Odour:	like: mineral oil.

#### Test method

##### Changes in the physical state

Initial boiling point and boiling range: not determined

Flash point: 180 °C DIN ISO 2592

Lower explosion limits: 0,6 vol. %



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### ADDINOL Gear Oil CLP 10

Print date: 07.05.2014

Product code: 741027

Page 5 of 7

Upper explosion limits:	7,0 vol. %
Ignition temperature:	not determined
Density (at 15 °C):	0,850 g/cm <sup>3</sup> DIN 51757
Water solubility:	virtually insoluble
Viscosity / kinematic: (at 40 °C)	10 mm <sup>2</sup> /s DIN 51562

## SECTION 10: Stability and reactivity

### 10.4. Conditions to avoid

Do not overheat to avoid decomposition by heat.  
Refer to chapter 7 No further action is necessary.

### 10.5. Incompatible materials

Reacts with :Oxidizing agents, strong.

### 10.6. Hazardous decomposition products

Can be released in case of fire: Carbon monoxide. Carbon dioxide (CO<sub>2</sub>). Nitrogen oxides (NO<sub>x</sub>).  
Carbon black.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Acute toxicity

No data available

Preparation not tested.

CAS No	Chemical name				
	Exposure routes	Method	Dose	Species	Source
64741-76-0	Distillates (petroleum), heavy hydrocracked; Base oil unspecified				
	oral	LD50	> 5000 mg/kg	Rat.	
	dermal	LD50	> 2000 mg/kg	Rabbit.	
	inhalative (4 h) vapour	LC50	> 5000 mg/l	Rabbit.	
4259-15-8	Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate).				
	oral	LD50	3100 mg/kg	Rat.	
	dermal	LD50	5000 mg/kg	Rabbit.	

#### Irritation and corrosivity

Irritant effect on the eye: Not an irritant.

Irritant effect on the skin: Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

#### Sensitising effects

Remark: no danger of sensitization.

#### Severe effects after repeated or prolonged exposure

Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

#### Carcinogenic/mutagenic/toxic effects for reproduction

No data available

#### Specific effects in experiment on an animal

No data available

## SECTION 12: Ecological information

### 12.1. Toxicity



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### ADDINOL Gear Oil CLP 10

Print date: 07.05.2014

Product code: 741027

Page 6 of 7

No data available

Preparation not tested.

CAS No	Chemical name					
	Aquatic toxicity	Method	Dose	[h]   [d]	Species	Source
64741-76-0	Distillates (petroleum), heavy hydrocracked; Base oil unspecified					
	Acute fish toxicity	LC50	> 100 mg/l	96 h	Fisch	
	Acute algae toxicity	ErC50	> = 100 mg/l	72 h	Alge	
4259-15-8	Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate).					
	Acute fish toxicity	LC50	1 - 10 mg/l	96 h	Carassius auratus (goldfish)	
	Acute algae toxicity	ErC50	240 mg/l	96 h		

#### 12.2. Persistence and degradability

Not easily bio-degradable (according to OECD-criteria). Do not empty into drains or the aquatic environment.

#### 12.3. Bioaccumulative potential

No data available

#### 12.4. Mobility in soil

Due to its low solubility in water the product is almost completely mechanically separated in biological waste water treatment plants.

#### 12.5. Results of PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

#### 12.6. Other adverse effects

No data available

#### Further information

Do not allow uncontrolled leakage of product into the environment.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

##### Advice on disposal

Must not be disposed of with domestic refuse. Do not empty into drains or the aquatic environment.

##### Waste disposal number of waste from residues/unused products

130205 OIL WASTES AND WASTES OF LIQUID FUELS (except edible oils, and those in chapters 05, 12 and 19); waste engine, gear and lubricating oils; mineral-based non-chlorinated engine, gear and lubricating oils  
Classified as hazardous waste.

##### Contaminated packaging

Contaminated packing must be completely emptied and can be re-used following appropriate cleaning. Packing which cannot be properly cleaned must be thrown away. Waste disposal according to official state regulations.

### SECTION 14: Transport information

#### Land transport (ADR/RID)

**14.1. UN number:** -

#### Inland waterways transport (ADN)

**14.1. UN number:** -

#### Marine transport (IMDG)



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### ADDINOL Gear Oil CLP 10

Print date: 07.05.2014

Product code: 741027

Page 7 of 7

**14.1. UN number:** -

**Air transport (ICAO)**

**14.1. UN number:** -

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: no

**Other applicable information**

Not a hazardous material with respect to these transportation regulations.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**National regulatory information**

Water contaminating class (D): 1 - slightly water contaminating

## SECTION 16: Other information

**Full text of R phrases referred to under Sections 2 and 3**

- |    |   |
|----|---|
| 41 | Risk of serious damage to eyes.                                 |
| 51 | Toxic to aquatic organisms.                                     |
| 53 | May cause long-term adverse effects in the aquatic environment. |
| 65 | Harmful: may cause lung damage if swallowed.                    |

**Full text of H statements referred to under Sections 2 and 3**

- |      |  |
|------|--|
| H304 | May be fatal if swallowed and enters airways.    |
| H318 | Causes serious eye damage.                       |
| H411 | Toxic to aquatic life with long lasting effects. |

**Further Information**

This preparation is hazardous in the sense of regulation (EC) No 1272/2008 [GHS].

These given data only refer to the named product. If the product is used together with other materials or in manufacturing processes the data might not be applicable any more. The data are based on today's state of our knowledge and experience. They are, however, no guarantee of any specific product properties and do not established any legally valid contractual relationship.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*