



according to Regulation (EC) No 1907/2006

ADDINOL Transmission Oil GX 80W-90 ML

Print date: 12.09.2014 Product code: 742030 Page 1 of 7

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

ADDINOL Transmission Oil GX 80W-90 ML

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Gearbox oil.

1.3. Details of the supplier of the safety data sheet

Company name: ADDINOL Lube Oil GmbH

Gebäude 4609

Street: Am Haupttor D-06237 Leuna Place:

Telephone: +49 (0) 3461 845-201 Telefax: +49 (0) 3461 845-561

e-mail: info@addinol.de Contact person: Application Technology

Internet: www.addinol.de

Responsible Department: **ADDINOL Application Technology**

1.4. Emergency telephone +49 (0) 3461 845-201 - This number is serviced during office hours.

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Indications of danger: Xi - Irritant

R phrases:

May cause sensitisation by skin contact.

GHS classification

Hazard categories:

Respiratory/skin sensitization: Skin Sens. 1

Hazard Statements:

Causes serious eye irritation. May cause an allergic skin reaction.

2.2. Label elements

Hazardous components which must be listed on the label

Contains: Pentene, 2,4,4-trimethyl-, sulfurized. May produce an allergic reaction.

Signal word: Warning Pictograms: GHS07



Hazard statements


H319 Causes serious eve irritation. H317 May cause an allergic skin reaction.

Precautionary statements

Avoid breathing dust/fume/gas/mist/vapours/spray. P261

P264 Wash hands thoroughly after handling.

Contaminated work clothing should not be allowed out of the workplace. P272





according to Regulation (EC) No 1907/2006

ADDINOL Transmission Oil GX 80W-90 ML

Print date: 12.09.2014 Product code: 742030 Page 2 of 7

P280 Wear suitable protective clothing and gloves.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.

Additional advice on labelling

This preparation is hazardous in the sense of regulation (EC) No 1272/2008 [GHS].

2.3. Other hazards

Prolonged/repetitive skin contact may cause skin defattening or dermatitis.

Spilled product must not leak into the ground.

Do not allow uncontrolled leakage of product into the environment.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

EC No	Chemical name	Quantity
CAS No	Classification	
Index No	GHS classification	
REACH No		
	Pentene, 2,4,4-trimethyl-, sulfurized	< 4,00 %
Polymer	Xi - Irritant R43-53	
	Skin Sens. 1, Aquatic Chronic 4; H317 H413	
931-384-6	Reaction products of bis(2-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched)	< 1,60 %
	Xn - Harmful, N - Dangerous for the environment R22-41-43-51-53	
	Flam. Liq. 3, Acute Tox. 4, Eye Dam. 1, Skin Sens. 1, Aquatic Chronic 2; H226 H302 H318 H317 H411	
01-2119493620-38		

Full text of R and H phrases: see Section 16.

Further Information

DMSO-Extrakt < 3 %, IP 346.

Concentration of PCBs < 1mg/kg.

Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Self-protection of the first aider.. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

After inhalation

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. In case of skin irritation, seek medical treatment.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.



ADDINOL Lube Oil GmbH

according to Regulation (EC) No 1907/2006

ADDINOL Transmission Oil GX 80W-90 ML

Print date: 12.09.2014 Product code: 742030 Page 3 of 7

After ingestion

Do not induce vomiting.

Rinse mouth thoroughly with water. Immediately get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Following symptoms can occur: Coughing. difficulties of breathing. Prolonged/repetitive skin contact may cause skin defattening or dermatitis.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam. Extinguishing powder. Carbon dioxide (CO2). Atomized water.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Can be released in case of fire: Carbon monoxide. Carbon dioxide (CO2). Sulfur oxides. Phosphorus oxides. Nitrogen oxides (NOx). Carbon black.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Extinguishing materials should be selected according to the surrounding area. Use water spray/stream to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately. Do not empty into drains or the aquatic environment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

High slip hazard because of leaking or spilled product. Remove all sources of ignition. Wear respiratory protection when in the presence of vapour, dust, and aerosols. Avoid contact with skin, eye and clothing.

6.2. Environmental precautions

Do not empty into drains or the aquatic environment. In case of gas being released or leakage into waters, ground or the drainage system, the appropriate authorities must be informed. Prevent spreading over great surfaces (e.g. by damming or installing oil booms).

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the assimilated material according to the section on waste disposal. Clean contaminated objects and areas thoroughly observing environmental regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Work in well ventilated zones or use proper respiratory protection. Avoid oil mist In case of open handling equipment with built-in suction must be used. Avoid contact with skin, eye and clothing.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

7.2. Conditions for safe storage, including any incompatibilities



ADDINOL Lube Oil GmbH

according to Regulation (EC) No 1907/2006

ADDINOL Transmission Oil GX 80W-90 ML

Print date: 12.09.2014 Product code: 742030 Page 4 of 7

Requirements for storage rooms and vessels

Keep the packing dry and well sealed to prevent contamination and absorbtion of dampness.

Advice on storage compatibility

Keep away from food, drink and animal feedingstuffs.

Keep away from: Oxidizing agents.

Further information on storage conditions

Recommended storage temperature: 10 - 30°C Protect against: heat. UV-radiation/sunlight. frost.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Additional advice on limit values

Recommended limit value for oil mist

TWA: 5 mg/m³ STEL: 10 mg/m³

The product does not contain any relevant quantities of substances with legally established exposure limitation.

8.2. Exposure controls





Appropriate engineering controls

Provide for sufficient ventilation and punctiform suction at critical points.

Protective and hygiene measures

Wash hands before breaks and at the end of work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): DIN EN 166

Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): DIN EN 374

Duration of wearing with permanent contact: 480 min

Suitable material: NBR (Nitrile rubber). Thickness of glove material: 0.7 mm.

Duration of wearing with occasional contact (splashes): 30 min

Suitable material: NBR (Nitrile rubber). Thickness of glove material: 0.4 mm

Protect skin by using skin protective cream.

Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

Respiratory protection

If technical suction or ventilation measures are not possible or are insufficient, protective breathing apparatus must be worn.



ADDINOL Lube Oil GmbH

according to Regulation (EC) No 1907/2006

ADDINOL Transmission Oil GX 80W-90 ML

Print date: 12.09.2014 Product code: 742030 Page 5 of 7

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid

Colour: yellow - brown
Odour: like: mineral oil.

Test method

Changes in the physical state

Initial boiling point and boiling range:

No data available

Flash point: 220 °C DIN EN ISO 2592

Ignition temperature: No data available

Density (at 15 °C): 0,897 g/cm³ DIN 51757

Water solubility: virtually insoluble

Viscosity / kinematic: 15,7 mm²/s DIN 51562

(at 100 °C)

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

No information available.

10.3. Possibility of hazardous reactions

No information available.

10.4. Conditions to avoid

Refer to chapter 7 No further action is necessary.

Do not overheat to avoid decomposition by heat.

10.5. Incompatible materials

Reacts with: Oxidizing agents, strong. Acid.

10.6. Hazardous decomposition products

Can be released in case of fire: Carbon monoxide. Carbon dioxide (CO2). Sulfur oxides. Phosphorus oxides. Nitrogen oxides (NOx). Carbon black.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

No data available

Mixture not tested.

CAS No	Chemical name					
	Exposure routes	Method	Dose	Species	Source	
	Reaction products of bis(2-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl (branched)					
	oral	ATE 5	500 mg/kg			

Irritation and corrosivity



ADDINOL Lube Oil GmbH

according to Regulation (EC) No 1907/2006

ADDINOL Transmission Oil GX 80W-90 ML

Print date: 12.09.2014 Product code: 742030 Page 6 of 7

Irritant effect on the eye: mild irritant.

Irritant effect on the skin: Prolonged/repetitive skin contact may cause skin defattening or dermatitis.

Sensitising effects

Contains: Pentene, 2,4,4-trimethyl-, sulfurized. May produce an allergic reaction.

Severe effects after repeated or prolonged exposure

Prolonged/repetitive skin contact may cause skin defattening or dermatitis.

Carcinogenic/mutagenic/toxic effects for reproduction

No data available

Specific effects in experiment on an animal

No data available

SECTION 12: Ecological information

12.1. Toxicity

No data available

Mixture not tested.

12.2. Persistence and degradability

Not easily bio-degradable (according to OECD-criteria). Do not empty into drains or the aquatic environment.

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

Due to its low solubility in water the product is almost completely mechanically separated in biological waste water treatment plants.

12.5. Results of PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

12.6. Other adverse effects

No data available

Further information

Do not allow uncontrolled leakage of product into the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Must not be disposed of with domestic refuse. Do not empty into drains or the aquatic environment.

Waste disposal number of waste from residues/unused products

130205 OIL WASTES AND WASTES OF LIQUID FUELS (except edible oils, and those in chapters 05, 12 and

19); waste engine, gear and lubricating oils; mineral-based non-chlorinated engine, gear and lubricating oils

Classified as hazardous waste.

Contaminated packaging

Contaminated packing must be completely emptied and can be re-used following appropriate cleaning. Waste disposal according to official state regulations. Packing which cannot be properly cleaned must be thrown away.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:



ADDINOL Lube Oil GmbH

according to Regulation (EC) No 1907/2006

ADDINOL Transmission Oil GX 80W-90 ML

Print date: 12.09.2014 Product code: 742030 Page 7 of 7

Inland waterways transport (ADN)

<u>14.1. UN number:</u>

Marine transport (IMDG)

14.1. UN number:

Air transport (ICAO)

14.1. UN number: -

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

Other applicable information

Not a hazardous material with respect to these transportation regulations.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulatory information

Water contaminating class (D): 1 - slightly water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Full text of R phrases referred to under Sections 2 and 3

- 22 Harmful if swallowed.
- 41 Risk of serious damage to eyes.
- 43 May cause sensitisation by skin contact.
- 51 Toxic to aquatic organisms.
- 53 May cause long-term adverse effects in the aquatic environment.

Full text of H statements referred to under Sections 2 and 3

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.

H413 May cause long lasting harmful effects to aquatic life.

Further Information

This preparation is hazardous in the sense of regulation (EC) No 1272/2008 [GHS].

These given data only refer to the named product. If the product is used together with other materials or in manufacturing processes the data might not be applicable any more. The data are based on today's state of our knowledge and experience. They are, however, no guarantee of any specific product properties and do not established any legally valid contructual relationship.

The receiver of our product is singulary responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)