

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Pole Protection Spray

Revision date: 15.08.2025

Product code: 717305

Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

ADDINOL Pole Protection Spray

UFI: SUJ2-82Q5-N20J-P0WN

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Aerosol - Corrosion inhibitor

1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name: ADDINOL Lube Oil GmbH
4609
Street: Am Haupttor
Place: D-06237 Leuna
Telephone: +49 (0) 3461 845-0
Telefax: +49 (0) 3461 845-555
E-mail: info@addinol.de
Contact person: Application Technology
Internet: www.addinol.de
Responsible Department: ADDINOL Application Technology

Supplier

Company name: ETL Fluid Experts Ltd.
Street: Grimbald Crag Road
Place: GB-HG5 8PY Knaresborough, North Yorkshire
Telephone: +44 (0)1423 522911
E-mail: sales(@)etlfe.com
Internet: https://www.etlfluidexperts.com/

1.4. Emergency telephone number:

+44 (0)1423 522911 - This number is serviced during office hours.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Aerosol 1; H222-H229
Skin Irrit. 2; H315
STOT SE 3; H336
Asp. Tox. 1; H304
Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

Signal word: Danger

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Pole Protection Spray

Revision date: 15.08.2025

Product code: 717305

Page 2 of 12

Pictograms:



Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P273	Avoid release to the environment.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents/container to an appropriate recycling or disposal facility.

Additional advice on labelling

Product is classified and labelled in accordance with EC regulations or the corresponding national laws.

2.3. Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Relevant ingredients

CAS No	Chemical name	Quantity
	EC No	Index No
		REACH No
	Classification (GB CLP Regulation)	
106-97-8	butane	20 - < 40 %
	203-448-7	601-004-00-0
	Flam. Gas 1, Liquefied gas; H220 H280	
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane	20 - < 40 %
	921-024-6	01-2119475514-35
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411	
74-98-6	propane	10 - < 20 %
	200-827-9	601-003-00-5
	Flam. Gas 1, Liquefied gas; H220 H280	

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
	921-024-6	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane	20 - < 40 %
	inhalation: LC50 = > 25,2 mg/l (vapours); dermal: LD50 = > 2800 - 3100 mg/kg; oral: LD50 = > 5000 mg/kg		

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Pole Protection Spray

Revision date: 15.08.2025

Product code: 717305

Page 3 of 12

Further Information

DMSO-Extract < 3 %; IP 346. Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove affected person from the danger area and lay down. Position and transport victim on their side. In case of respiratory distress, bring into semi-upright, seated position. Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

After inhalation

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist. In case of breathing difficulties administer oxygen.

After contact with skin

Take off immediately all contaminated clothing, including underwear and shoes. After contact with skin, wash immediately with plenty of water and soap. In case of skin irritation, seek medical treatment.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of troubles or persistent symptoms, consult an ophthalmologist.

After ingestion

Do NOT induce vomiting.

Rinse mouth thoroughly with water. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

following inhalation: drowsiness. Headache. Nausea.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂). Extinguishing powder. Foam.

Unsuitable extinguishing media

Water.

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon dioxide (CO₂). Carbon monoxide Nitrogen oxides (NO_x). carbon black.

Vapours may form explosive mixtures with air.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray jet to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Remove persons to safety. Wear a self-contained breathing apparatus and chemical resistant suit. Vapours are

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Pole Protection Spray

Revision date: 15.08.2025

Product code: 717305

Page 4 of 12

heavier than air and will spread at floor level. Avoid contact with skin and eyes. Keep away from sources of ignition - No smoking.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Prevent spread over a wide area (e.g. by containment or oil barriers).

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Collect in closed containers for disposal. Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Section 12: Ecological Information (non-mandatory)

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means. Take precautionary measures against static discharges. Do not spray on naked flames or any incandescent material. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Avoid contact with skin, eyes and clothes.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Heating causes rise in pressure with risk of bursting.

Advice on general occupational hygiene

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep the packing dry and well sealed to prevent contamination and absorption of humidity. Keep container tightly closed in a cool place. Keep away from sources of ignition - No smoking.

Please note: TRG 300, aerosol directive (75/324/EEC).

Hints on joint storage

Keep away from food, drink and animal feedingstuffs.

Keep away from: Oxidizing agent. Material, rich in oxygen, oxidizing.

Further information on storage conditions

Recommended storage temperature: 5 - 40°C. Do not store at temperatures over: 50°C.

7.3. Specific end use(s)

Further information: see technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Pole Protection Spray

Revision date: 15.08.2025

Product code: 717305

Page 5 of 12

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane			
Worker DNEL, long-term		inhalation	systemic	2035 mg/m ³
Worker DNEL, long-term		dermal	systemic	773 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	608 mg/m ³
Consumer DNEL, long-term		dermal	systemic	699 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	699 mg/kg bw/day

Additional advice on limit values

source:

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.

Individual protection measures, such as personal protective equipment

Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): EN 166

Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): EN ISO 374

Duration of wearing with permanent contact: 480 min

Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.7 mm.

Wearing time with occasional contact (splashes): 30 min

Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.4 mm

Protect skin by using skin protective cream.

Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Breathing protection with filter against organic gases and vapours type A - boiling point > 65°C: A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Pole Protection Spray

Revision date: 15.08.2025

Product code: 717305

Page 6 of 12

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	gaseous
Colour:	blue
Odour:	characteristic
Odour threshold:	not determined

	Test method
Melting point/freezing point:	not applicable
Boiling point or initial boiling point and boiling range:	< -20 °C
Flammability:	not applicable
Lower explosion limits:	0,6 vol. %
Upper explosion limits:	10,9 vol. %
Flash point:	< -20 °C DIN EN ISO 2592
Auto-ignition temperature:	> 200 °C DIN 51794
Decomposition temperature:	not determined
pH-Value:	not applicable
Viscosity / kinematic:	not applicable
Water solubility: (at 20 °C)	insoluble
Solubility in other solvents No data available	
Partition coefficient n-octanol/water:	not determined
Vapour pressure: (at 20 °C)	not determined
Density (at 20 °C):	0,613 g/cm ³ DIN 51757
Relative vapour density:	No data available
Particle characteristics:	No data available

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

evaluation: not Explosive.

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

Sustained combustibility:

No data available

Self-ignition temperature

Solid:

not applicable

Gas:

not applicable

Oxidizing properties

Not oxidising.

Other safety characteristics

Evaporation rate:

not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

Ignition hazard.

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Pole Protection Spray

Revision date: 15.08.2025

Product code: 717305

Page 7 of 12

Vapours may form explosive mixtures with air.

10.4. Conditions to avoid

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children. Take precautionary measures against static discharges.

10.5. Incompatible materials

Keep away from: Oxidizing agents. Material, rich in oxygen, oxidizing.

10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon dioxide (CO₂). Carbon monoxide Nitrogen oxides (NO_x). carbon black.

Combustible. Vapours may form explosive mixtures with air.

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in GB CLP Regulation****Acute toxicity**

Based on available data, the classification criteria are not met.
Mixture not tested.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation gas) > 20000 ppm

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane				
	oral	LD50 > 5000 mg/kg	Rat		
	dermal	LD50 > 2800 - 3100 mg/kg	Rat	Study report (1977)	The acute toxicity of SBP 100/140 was de
	inhalation (4 h) vapour	LC50 > 25,2 mg/l	Rat	Study report (1988)	Group of rats were exposed to test subst

Irritation and corrosivity

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

11.2. Information on other hazards**Endocrine disrupting properties**

not applicable

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Pole Protection Spray

Revision date: 15.08.2025

Product code: 717305

Page 8 of 12

Further information

If handled with proper care and at intended use, the product does not cause any harmful effects acc. to our experiences and available information.

SECTION 12: Ecological information

12.1. Toxicity

Toxic to aquatic life with long lasting effects.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
106-97-8	butane					
	Acute fish toxicity	LC50 mg/l	49,9	96 h	Fish, no other information	United States Environmental Protection A The Ecosar class program has been develo
	Acute algae toxicity	ErC50 mg/l	19,37	96 h	Algae	USEPA OPPT Risk Assessment Division (200 Calculation using ECOSAR Program v1.00.
	Acute crustacea toxicity	EC50 mg/l	69,43	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200 Calculation using ECOSAR Program v1.00.
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane					
	Acute fish toxicity	LC50 mg/l	11,40	96 h	Oncorhynchus mykiss (Rainbow trout)	
	Acute algae toxicity	ErC50 mg/l	10 - 30	72 h	Pseudokirchneriella subcapitata	Study report (1995) OECD Guideline 201
	Acute crustacea toxicity	EC50	3 mg/l	48 h	Daphnia magna	
	Fish toxicity	NOEC mg/l	2,045	28 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010) The aquatic toxicity was estimated by a
	Crustacea toxicity	NOEC	1 mg/l	21 d	Daphnia magna	SIDS Initial Assessment Report For SIAM OECD Guideline 211
74-98-6	propane					
	Acute fish toxicity	LC50 mg/l	49,9	96 h	Fish, no other information	United States Environmental Protection A The Ecosar class program has been develo
	Acute algae toxicity	ErC50 mg/l	19,37	96 h	Algae	USEPA OPPT Risk Assessment Division (200 Calculation using ECOSAR Program v1.00.
	Acute crustacea toxicity	EC50 mg/l	69,43	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200 Calculation using ECOSAR Program v1.00.

12.2. Persistence and degradability

Not easily bio-degradable (according to OECD-criteria). Do not allow to enter into surface water or drains.

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
106-97-8	butane	1,09
74-98-6	propane	1,09

12.4. Mobility in soil

Product is easily volatile. The test was carried out in a closed test system. Product is difficult to dissolve in water.

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Pole Protection Spray

Revision date: 15.08.2025

Product code: 717305

Page 9 of 12

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Do not open container by force. Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

Contaminated packaging

Dispose of waste according to applicable legislation.

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number or ID number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
 Hazard label: 2.1



Classification code: 5F
 Special Provisions: 190 327 344 625
 Limited quantity: 1 L
 Excepted quantity: E0
 Transport category: 2
 Tunnel restriction code: D

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
 Hazard label: 2.1



Classification code: 5F
 Special Provisions: 190 327 344 625
 Limited quantity: 1 L
 Excepted quantity: E0

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Pole Protection Spray

Revision date: 15.08.2025

Product code: 717305

Page 10 of 12

Marine transport (IMDG)

14.1. UN number or ID number:	UN 1950
14.2. UN proper shipping name:	AEROSOLS
14.3. Transport hazard class(es):	2.1
14.4. Packing group:	-
Hazard label:	2.1



Special Provisions:	63, 190, 277, 327, 344, 959
Limited quantity:	1000 mL
Excepted quantity:	E0
EmS:	F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:	UN 1950
14.2. UN proper shipping name:	AEROSOLS, flammable
14.3. Transport hazard class(es):	2.1
14.4. Packing group:	-
Hazard label:	2.1



Special Provisions:	A145 A167 A802
Limited quantity Passenger:	30 kg G
Passenger LQ:	Y203
Excepted quantity:	E0
IATA-packing instructions - Passenger:	203
IATA-max. quantity - Passenger:	75 kg
IATA-packing instructions - Cargo:	203
IATA-max. quantity - Cargo:	150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes



Danger releasing substance: HYDROCARBONS, LIQUID, N.O.S.

14.6. Special precautions for user

Warning: flammable gases.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 28, Entry 40, Entry 75

Directive 2010/75/EU on industrial emissions: 87,946 % (539,111 g/L)

Directive 2004/42/EC on VOC in paints and varnishes: 87,946 % (539,111 g/L)

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Pole Protection Spray

Revision date: 15.08.2025

Product code: 717305

Page 11 of 12

Information according to Directive 2012/18/EU (SEVESO III): P3a FLAMMABLE AEROSOLS

Additional information: E2

Additional information

To follow: 850/2004/EC, 1107/2009/EC, 649/2012/EC, Aerosolrichtlinie (75/324/EWG)

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 3,5,6,7,9,10,11,12,16.

Abbreviations and acronyms

Flam. Gas: Flammable gases

Aerosol: Aerosols

Liquefied gas

Flam. Liq: Flammable liquids

Asp. Tox: Aspiration hazard

Skin Irrit: Skin irritation

STOT SE: Specific target organ toxicity - single exposure

Aquatic Chronic: Chronic aquatic hazard

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ASTM - American Society for the Testing of Materials; ATE - Acute Toxicity Estimates; bw - Body weight; CAO - Cargo Aircraft Only; CAS - Chemical Abstracts Service; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DNEL - Derived No-Effect Level; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); EG - European Union; EN - European standards; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISO - International Organisation for Standardization; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; OECD - Organization for Economic Co-operation and Development; PBT - Persistent, Bioaccumulative and Toxic substance; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulation concerning the International Carriage of Dangerous Goods by Rail; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Pole Protection Spray

Revision date: 15.08.2025

Product code: 717305

Page 12 of 12

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Aerosol 1; H222-H229	
Skin Irrit. 2; H315	Calculation method
STOT SE 3; H336	Calculation method
Asp. Tox. 1; H304	Calculation method
Aquatic Chronic 2; H411	Calculation method

Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Further Information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)