

according to Regulation (EC) No 1907/2006

## **ADDINOL Corrosion Protection Fluid KO 6 F Spray**

Print date: 08.10.2014 Product code: 773002 Page 1 of 10

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

ADDINOL Corrosion Protection Fluid KO 6 F Spray

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Aerosol - Corrosion inhibitor.

## 1.3. Details of the supplier of the safety data sheet

Company name: ADDINOL Lube Oil GmbH

Gebäude 4609

Street: Am Haupttor
Place: D-06237 Leuna

Telephone: +49 (0) 3461 845-201 Telefax: +49 (0) 3461 845-561

e-mail: info@addinol.de

Contact person: Application Technology

Internet: www.addinol.de

Responsible Department: ADDINOL Application Technology

1.4. Emergency telephone +49 (0) 3461 845-201 - This number is serviced during office hours.

number:

## **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

Indications of danger: F+ - Extremely flammable

R phrases:

Extremely flammable.

Repeated exposure may cause skin dryness or cracking.

#### **GHS** classification

Hazard categories: Aerosol: Aerosol 1 Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated.

#### 2.2. Label elements

Signal word: Danger Pictograms: GHS02



## **Hazard statements**

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

**Precautionary statements** 

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smokina.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.



ADDINOL Lube Oil GmbH

according to Regulation (EC) No 1907/2006

## **ADDINOL Corrosion Protection Fluid KO 6 F Spray**

Print date: 08.10.2014 Product code: 773002 Page 2 of 10

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

## Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.

### Additional advice on labelling

This preparation is hazardous in the sense of regulation (EC) No 1272/2008 [GHS].

#### 2.3. Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

## **SECTION 3: Composition/information on ingredients**

### 3.2. Mixtures

#### **Hazardous components**

Chemical name	Quantity
Classification	
GHS classification	
butane	< 40 %
F+ - Extremely flammable R12	
Flam. Gas 1; H220	
Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclics, < 2% aromatics	< 25 %
Xn - Harmful R65-66	
Asp. Tox. 1; H304	
propane	< 20 %
F+ - Extremely flammable R12	_
Flam. Gas 1; H220	
	Classification GHS classification  butane F+ - Extremely flammable R12 Flam. Gas 1; H220  Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclics, < 2% aromatics Xn - Harmful R65-66 Asp. Tox. 1; H304  propane F+ - Extremely flammable R12

Full text of R and H phrases: see Section 16.

## **Further Information**

DMSO-Extrakt < 3 %, IP 346.

Concentration of PCBs < 1mg/kg.

Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

## **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

### **General information**

Move victim out of danger zone and lay down. Position and transport victim on their side. In case of respiratory distress, bring into semi-upright, seated position. Self-protection of the first aider.. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

#### After inhalation

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist. In case of breathing difficulties administer oxygen.

## After contact with skin

After contact with skin, wash immediately with plenty of water and soap. In case of skin irritation, seek medical treatment.



ADDINOL Lube Oil GmbH

according to Regulation (EC) No 1907/2006

## **ADDINOL Corrosion Protection Fluid KO 6 F Spray**

Print date: 08.10.2014 Product code: 773002 Page 3 of 10

#### After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of troubles or persistent symptoms, consult an ophthalmologist.

#### After ingestion

Do not induce vomiting.

Rinse mouth thoroughly with water. Immediately get medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

following inhalation: drowsiness. Headache. Nausea.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

#### Suitable extinguishing media

Carbon dioxide (CO2). Dry extinguishing powder. alcohol resistant foam.

#### Unsuitable extinguishing media

High power water jet.

#### 5.2. Special hazards arising from the substance or mixture

Can be released in case of fire: Carbon dioxide (CO2). Carbon monoxide. Nitrogen oxides (NOx). Carbon black.

Vapours may form explosive mixtures with air.

## 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Wear chemical resistant suit.

#### **Additional information**

Extinguishing materials should be selected according to the surrounding area. Use water spray/stream to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately.

### **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

Guide people to safety. Wear a self-contained breathing apparatus and chemical resistant suit. Vapours are heavier than air and will spread at floor level. Avoid contact with skin and eyes. Keep away from sources of ignition - No smoking.

## 6.2. Environmental precautions

Do not empty into drains or the aquatic environment. In case of gas being released or leakage into waters, ground or the drainage system, the appropriate authorities must be informed. Prevent spreading over great surfaces (e.g. by damming or installing oil booms).

## 6.3. Methods and material for containment and cleaning up


Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the assimilated material according to the section on waste disposal. Clean contaminated objects and areas thoroughly observing environmental regulations.

#### 6.4. Reference to other sections

Refer to the provisions listed in Sections 8, 12 and 13.

#### **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling





according to Regulation (EC) No 1907/2006

## **ADDINOL Corrosion Protection Fluid KO 6 F Spray**

Print date: 08.10.2014 Product code: 773002 Page 4 of 10

#### Advice on safe handling

Work in well ventilated zones or use proper respiratory protection. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Do not spray into flames or ignition sources.

### Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Heating causes rise in pressure with risk of bursting.

#### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep the packing dry and well sealed to prevent contamination and absorbtion of dampness. Keep container tightly closed in a cool place. Keep away from sources of ignition - No smoking.

Please note: TRG 300, aerosol directive (75/324/EEC).

## Advice on storage compatibility

Keep away from food, drink and animal feedingstuffs.

Keep away from: Oxidizing agents. Material, rich in oxygen, oxidizing.

#### Further information on storage conditions

Recommended storage temperature: 10 - 30°C. Do not store at temperatures over: 50°C.

#### 7.3. Specific end use(s)

Further information: refer to Technical Data Sheet.

## **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

### **Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
64742-48-9	Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclics, < 2% aromatics	200			TWA (8 h)	MAK
					STEL (15 min)	MAK
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL

#### Additional advice on limit values

source:

### 8.2. Exposure controls





### Appropriate engineering controls

Provide for sufficient ventilation and punctiform suction at critical points.

## Protective and hygiene measures

Wash hands before breaks and at the end of work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

#### Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): DIN EN 166





according to Regulation (EC) No 1907/2006

## **ADDINOL Corrosion Protection Fluid KO 6 F Spray**

Print date: 08.10.2014 Product code: 773002 Page 5 of 10

### Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): DIN EN 374

Duration of wearing with permanent contact: 480 min

Suitable material: NBR (Nitrile rubber). Thickness of glove material: 0.7 mm.

Duration of wearing with occasional contact (splashes): 30 min

Suitable material: NBR (Nitrile rubber). Thickness of glove material: 0.4 mm

Protect skin by using skin protective cream.

## Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

### Respiratory protection

If technical suction or ventilation measures are not possible or are insufficient, protective breathing apparatus must be worn. Breathing protection with filter against organic gases and vapours type A - boiling point > 65°C: A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

### **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state: gaseous
Colour: light brown
Odour: like: mineral oil.

Test method

Changes in the physical state

Initial boiling point and boiling range: < -20 °C

Flash point: < -20 °C DIN EN ISO 2592

**Explosive properties** 

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

Lower explosion limits: 0,6 vol. %
Upper explosion limits: 10,8 vol. %
Ignition temperature: 210 °C

Oxidizing properties

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

Density (at 15 °C): 0,646 g/cm³ calculated

Water solubility: insoluble

(at 20 °C)

Viscosity / kinematic: not applicable DIN 51562

#### **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

Stable with proper care and handling.

## 10.2. Chemical stability

The product is chemically stable when handled and stored under normal conditions.



ADDINOL Lube Oil GmbH

according to Regulation (EC) No 1907/2006

## **ADDINOL Corrosion Protection Fluid KO 6 F Spray**

Print date: 08.10.2014 Product code: 773002 Page 6 of 10

#### 10.3. Possibility of hazardous reactions

Ignition hazard.

Vapours may form explosive mixtures with air.

#### 10.4. Conditions to avoid

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children. Take precautionary measures against static discharges. See protective measures under point 7 and 8.

#### 10.5. Incompatible materials

Keep away from: Oxidizing agents. Material, rich in oxygen, oxidizing.

#### 10.6. Hazardous decomposition products

Can be released in case of fire: Carbon dioxide (CO2). Carbon monoxide. Nitrogen oxides (NOx). Carbon black.

Vapours may form explosive mixtures with air.

## **SECTION 11: Toxicological information**

## 11.1. Information on toxicological effects

#### **Acute toxicity**

No data available

Preparation not tested.

CAS No	Chemical name						
	Exposure routes	Method	Dose	Species	Source		
106-97-8	butane						
	inhalative (4 h) gas	LC50	273000 ppm	Rat	GESTIS		
64742-48-9	Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclics, < 2% aromatics						
	oral	LD50	> 5000 mg/kg	Rat.			
	dermal	LD50	> 5000 mg/kg	Rabbit.			

### Irritation and corrosivity

Irritant effect on the eye: mild irritant.

Irritant effect on the skin: Prolonged/repetitive skin contact may cause skin defattening or dermatitis.

# Sensitising effects

Evaluation: no danger of sensitization.

## STOT-single exposure

Vapours may cause drowsiness and dizziness.

## Severe effects after repeated or prolonged exposure

Prolonged/repetitive skin contact may cause skin defattening or dermatitis.

# Carcinogenic/mutagenic/toxic effects for reproduction

No data available

## Specific effects in experiment on an animal

following inhalation: drowsiness. Headache. unconsciousness.

## **Further information**

If handled with proper care and at intended use, the product does not cause any harmful effects acc. to our experiences and available information.





according to Regulation (EC) No 1907/2006

## **ADDINOL Corrosion Protection Fluid KO 6 F Spray**

Print date: 08.10.2014 Product code: 773002 Page 7 of 10

## **SECTION 12: Ecological information**

#### 12.1. Toxicity

No data available

Mixture not tested.

CAS No	Chemical name								
	Aquatic toxicity	Method	Dose	[h]   [d]	Species	Source			
64742-48-9	Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclics, < 2% aromatics								
	Acute fish toxicity	LC50	1000 mg/l	96 h	Oncorhynchus mykiss				
	Acute algae toxicity	ErC50	1000 mg/l		Pseudokirchneriella subcapitata				

## 12.2. Persistence and degradability

Not easily bio-degradable (according to OECD-criteria). Do not empty into drains or the aquatic environment.

#### 12.3. Bioaccumulative potential

No data available

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
106-97-8	butane	2,89
74-98-6	propane	2,36

#### 12.4. Mobility in soil

Product is easily volatile. Product is difficult to dissolve in water.

## 12.5. Results of PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

### 12.6. Other adverse effects

No data available

# **SECTION 13: Disposal considerations**

## 13.1. Waste treatment methods

#### Advice on disposal

Must not be disposed of with domestic refuse. Do not empty into drains or the aquatic environment.

### Waste disposal number of waste from residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded

chemicals; gases in pressure containers (including halons) containing dangerous substances

Classified as hazardous waste.

# Contaminated packaging

Waste disposal according to official state regulations.

### **SECTION 14: Transport information**

#### Land transport (ADR/RID)

14.1. UN number:UN 195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es):214.4. Packing group:-Hazard label:2.1



according to Regulation (EC) No 1907/2006

## **ADDINOL Corrosion Protection Fluid KO 6 F Spray**

Print date: 08.10.2014 Product code: 773002 Page 8 of 10



Classification code: 5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L
Transport category: 2
Tunnel restriction code: D

Other applicable information (land transport)

Quantities released: E0

Special provisions: 190 - 327 - 625

Transportation category: 2 Tunnel restriction code: B1D

## Inland waterways transport (ADN)

14.1. UN number:UN 195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es):214.4. Packing group:-Hazard label:2.1



Classification code: 5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L

## Other applicable information (inland waterways transport)

Quantities released: E0 Special provisions: 190 327 625

## Marine transport (IMDG)

14.1. UN number:UN 195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1



Special Provisions: 63, 190, 277, 327, 344, 959

Limited quantity: See SP277 EmS: F-D, S-U

#### Other applicable information (marine transport)

Quantities released: E0

Special provisions: 63, 190, 277, 327, 959

## Air transport (ICAO)

**14.1. UN number:** UN 1950

14.2. UN proper shipping name: AEROSOLS, flammable

14.3. Transport hazard class(es): 2.1





according to Regulation (EC) No 1907/2006

## **ADDINOL Corrosion Protection Fluid KO 6 F Spray**

Print date: 08.10.2014 Product code: 773002 Page 9 of 10

14.4. Packing group:

Hazard label: 2.1



Special Provisions: A145 A167 A802

Limited quantity Passenger: 30 kg G

IATA-packing instructions - Passenger:203IATA-max. quantity - Passenger:75 kgIATA-packing instructions - Cargo:203IATA-max. quantity - Cargo:150 kg

Other applicable information (air transport)

Passenger LQ: Y203 Quantities released: E0

Danger: Y203

Special provisions: A145 - A153

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

Warning: Flammable gases.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

not applicable

## **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### **National regulatory information**

Employment restrictions: Observe employment restrictions for young people.

Water contaminating class (D): 1 - slightly water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

#### **SECTION 16: Other information**

#### Full text of R phrases referred to under Sections 2 and 3

12 Extremely flammable.

Harmful: may cause lung damage if swallowed.

Repeated exposure may cause skin dryness or cracking.

### Full text of H statements referred to under Sections 2 and 3

H220 Extremely flammable gas. H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.
H304 May be fatal if swallowed and enters airways.

#### **Further Information**

This preparation is hazardous in the sense of regulation (EC) No 1272/2008 [GHS].

These given data only refer to the named product. If the product is used together with other materials or in manufacturing processes the data might not be applicable any more. The data are based on today's state of our knowledge and experience. They are, however, no guarantee of any specific product properties and do not established any legally valid contructual relationship.





according to Regulation (EC) No 1907/2006

## **ADDINOL Corrosion Protection Fluid KO 6 F Spray**

Print date: 08.10.2014 Product code: 773002 Page 10 of 10

The receiver of our product is singulary responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)