

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Gear Oil 150 F

Revision date: 10.05.2023

Product code: 741121

Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

ADDINOL Gear Oil 150 F

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Gearbox oil.

1.3. Details of the supplier of the safety data sheet**Manufacturer**

Company name:	ADDINOL Lube Oil GmbH	
	Gebäude 4609	
Street:	Am Haupttor	
Place:	D-06237 Leuna	
Telephone:	+49 (0) 3461 845-0	Telefax: +49 (0) 3461 845-555
e-mail:	info@addinol.de	
Contact person:	Application Technology	
Internet:	www.addinol.de	
Responsible Department:	ADDINOL Application Technology	

Supplier

Company name:	Gidov Oil & Logistics Ltd.	
Street:	76 Cobham Road, Ferndown Industrial Estate	
Place:	GB-TN157DA Wrotham, Sevenoaks Kent	
Telephone:	+44 7729229830	Telefax: +44 7729229830
e-mail:	sales@addinol.co.uk	
Internet:	https://www.gidovlogistics.co.uk/	

1.4. Emergency telephone number:

+44 7729229830 - This number is serviced during office hours.

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****GB CLP Regulation**

This mixture is not classified as hazardous in accordance with GB CLP Regulation.

2.2. Label elements**GB CLP Regulation****Special labelling of certain mixtures**

EUH210 Safety data sheet available on request.

Additional advice on labelling

Product is classified and labelled in accordance with EC regulations or the corresponding national laws.

2.3. Other hazards

Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

Spilled product must not leak into the ground.

Do not allow uncontrolled leakage of product into the environment.

SECTION 3: Composition/information on ingredients**3.2. Mixtures**

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Gear Oil 150 F

Revision date: 10.05.2023

Product code: 741121

Page 2 of 10

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified			60 - < 80 %
	265-157-1		01-2119484627-25	
	Asp. Tox. 1; H304			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
64742-54-7	265-157-1	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified	60 - < 80 %
	dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg		

Further Information

DMSO-Extrakt < 3 %, IP 346.

Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

After inhalation

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. In case of skin irritation, seek medical treatment.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

After ingestion

Do NOT induce vomiting. Rinse mouth immediately and drink plenty of water. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Foam. Extinguishing powder. Carbon dioxide (CO₂). Atomized water.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO₂). Sulfur oxides. Phosphorus oxides.

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Gear Oil 150 F

Revision date: 10.05.2023

Product code: 741121

Page 3 of 10

Nitrogen oxides (NO_x), carbon black.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray/stream to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

High slip hazard because of leaking or spilled product. Remove all sources of ignition. Wear breathing apparatus if exposed to vapours/dusts/aerosols. Avoid contact with skin, eye and clothing.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Prevent spread over a wide area (e.g. by containment or oil barriers).

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Section 12: Ecological Information (non-mandatory)

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Work in well-ventilated zones or use proper respiratory protection. Avoid oil mist. If handled uncovered, arrangements with local exhaust ventilation have to be used. Avoid contact with skin, eyes and clothes.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Advice on general occupational hygiene

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep the packing dry and well sealed to prevent contamination and absorption of humidity. Keep container tightly closed in a cool place. Keep/Store only in original container.

Hints on joint storage

Keep away from food, drink and animal feedingstuffs.

Keep away from: Oxidizing agent

Further information on storage conditions

Protect against: UV-radiation/sunlight, frost, heat.

Recommended storage temperature: 5 - 40°C

7.3. Specific end use(s)

Further information: see technical data sheet.

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Gear Oil 150 F

Revision date: 10.05.2023

Product code: 741121

Page 4 of 10

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
104-76-7	2-ethylhexan-1-ol	1	5.4		TWA (8 h)	WEL

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified			
	Worker DNEL, long-term	inhalation	systemic	2,73 mg/m ³
	Worker DNEL, long-term	inhalation	local	5,58 mg/m ³
	Worker DNEL, long-term	dermal	systemic	0,97 mg/kg bw/day
	Consumer DNEL, long-term	inhalation	local	1,19 mg/m ³
	Consumer DNEL, long-term	oral	systemic	0,74 mg/kg bw/day
104-76-7	2-Ethylhexan-1-ol			
	Worker DNEL, long-term	inhalation	systemic	12,8 mg/m ³
	Worker DNEL, long-term	inhalation	local	53,2 mg/m ³
	Worker DNEL, acute	inhalation	local	53,2 mg/m ³
	Worker DNEL, long-term	dermal	systemic	23 mg/kg bw/day
	Consumer DNEL, long-term	inhalation	systemic	2,3 mg/m ³
	Consumer DNEL, long-term	inhalation	local	26,6 mg/m ³
	Consumer DNEL, acute	inhalation	local	26,6 mg/m ³
	Consumer DNEL, long-term	dermal	systemic	11,4 mg/kg bw/day
	Consumer DNEL, long-term	oral	systemic	1,1 mg/kg bw/day

PNEC values

CAS No	Substance	Value
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified	
	Secondary poisoning	9,33 mg/kg
104-76-7	2-Ethylhexan-1-ol	
	Freshwater	0,017 mg/l
	Freshwater (intermittent releases)	0,17 mg/l
	Marine water	0,002 mg/l
	Freshwater sediment	0,284 mg/kg
	Marine sediment	0,028 mg/kg
	Secondary poisoning	55 mg/kg
	Micro-organisms in sewage treatment plants (STP)	10 mg/l
	Soil	0,047 mg/kg

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Gear Oil 150 F

Revision date: 10.05.2023

Product code: 741121

Page 5 of 10

Additional advice on limit values

Recommended limit value for oil mist

TWA: 5 mg/m³STEL: 10 mg/m³

The product does not contain any relevant quantities of substances with legally established exposure limitation.

8.2. Exposure controls**Appropriate engineering controls**

Provide adequate ventilation as well as local exhaustion at critical locations.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): EN 166

Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): EN ISO 374

Duration of wearing with permanent contact: 480 min

Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.7 mm.

Wearing time with occasional contact (splashes): 30 min

Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.4 mm

Protect skin by using skin protective cream.

Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Breathing protection with filter against organic gases and vapours type A - boiling point > 65°C: A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	liquid
Colour:	yellow - brown
Odour:	like: mineral oil.
Odour threshold:	not determined

	Test method
Melting point/freezing point:	No data available
Boiling point or initial boiling point and boiling range:	No data available
Flammability:	No data available
Lower explosion limits:	No data available
Upper explosion limits:	No data available
Flash point:	250 °C DIN EN ISO 2592

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Gear Oil 150 F

Revision date: 10.05.2023

Product code: 741121

Page 6 of 10

Auto-ignition temperature:	No data available
Decomposition temperature:	No data available
pH-Value:	not applicable
Viscosity / kinematic: (at 40 °C)	150 mm ² /s ASTM D 7042
Water solubility:	virtually insoluble
Solubility in other solvents	
No data available	
Partition coefficient n-octanol/water:	No data available
Vapour pressure:	No data available
Density (at 15 °C):	0,890 g/cm ³ DIN 51757
Relative vapour density:	No data available

9.2. Other information**Information with regard to physical hazard classes**

Explosive properties

No data available

Self-ignition temperature

Solid:

No data available

Gas:

No data available

Oxidizing properties

No data available

Other safety characteristics

Evaporation rate:

No data available

Pour point:

-23 °C ASTM D 7346

SECTION 10: Stability and reactivity**10.1. Reactivity**

The product is stable under storage at normal ambient temperatures.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Refer to chapter 7 No further action is necessary.

Do not overheat to avoid decomposition by heat.

10.5. Incompatible materials

Reacts with: Oxidising agent, strong

10.6. Hazardous decomposition productsIn case of fire may be liberated: Carbon monoxide Carbon dioxide (CO₂). Sulfur oxides. Phosphorus oxides.Nitrogen oxides (NO_x). carbon black.

No known hazardous decomposition products.

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in GB CLP Regulation****Acute toxicity**

Based on available data, the classification criteria are not met.

Mixture not tested.

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Gear Oil 150 F

Revision date: 10.05.2023

Product code: 741121

Page 7 of 10

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1982)	OECD Guideline 401
	dermal	LD50 > 5000 mg/kg	Rabbit	Study report (1982)	OECD Guideline 402

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards**Endocrine disrupting properties**

not applicable

SECTION 12: Ecological information**12.1. Toxicity**

Based on available data, the classification criteria are not met.

Mixture not tested.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified					
	Acute fish toxicity	LL50 > 100 mg/l	96 h	Pimephales promelas	Study report (1995)	OECD Guideline 203
	Acute algae toxicity	ErC50 >100 mg/l	72 h			
	Fish toxicity	NOEC >= 1000 mg/l	14 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)	The aquatic toxicity was estimated by a

12.2. Persistence and degradability

Not easily bio-degradable (according to OECD-criteria). Do not allow to enter into surface water or drains.

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

Due to its low solubility in water the product is almost completely mechanically separated in biological waste water treatment plants.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Gear Oil 150 F

Revision date: 10.05.2023

Product code: 741121

Page 8 of 10

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No data available

Further information

Do not allow uncontrolled leakage of product into the environment.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

List of Wastes Code - residues/unused products

130205 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; mineral-based non-chlorinated engine, gear and lubricating oils; hazardous waste

Contaminated packaging

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Dispose of waste according to applicable legislation. Packing which cannot be properly cleaned must be thrown away.

SECTION 14: Transport information**Land transport (ADR/RID)**

- 14.1. UN number or ID number:** -
14.2. UN proper shipping name: -
14.3. Transport hazard class(es): -
14.4. Packing group: -

Inland waterways transport (ADN)

- 14.1. UN number or ID number:** -
14.2. UN proper shipping name: -
14.3. Transport hazard class(es): -
14.4. Packing group: -

Marine transport (IMDG)

- 14.1. UN number or ID number:** -
14.2. UN proper shipping name: -
14.3. Transport hazard class(es): -
14.4. Packing group: -

Air transport (ICAO-TI/IATA-DGR)

- 14.1. UN number or ID number:** -
14.2. UN proper shipping name: -
14.3. Transport hazard class(es): -
14.4. Packing group: -

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

Other applicable information

No dangerous good in sense of these transport regulations.

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Gear Oil 150 F

Revision date: 10.05.2023

Product code: 741121

Page 9 of 10

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****National regulatory information**

Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 1,4,6,7,9,10,11,12,16.

Abbreviations and acronyms

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ASTM - American Society for the Testing of Materials; ATE - Acute Toxicity Estimates; bw - Body weight; CAO - Cargo Aircraft Only; CAS - Chemical Abstracts Service; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DNEL - Derived No-Effect Level; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); EG - European Union; EN - European standards; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISO - International Organisation for Standardization; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n;o;s; - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; OECD - Organization for Economic Co-operation and Development; PBT - Persistent, Bioaccumulative and Toxic substance; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulation concerning the International Carriage of Dangerous Goods by Rail; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Relevant H and EUH statements (number and full text)

H304 May be fatal if swallowed and enters airways.
 EUH210 Safety data sheet available on request.

Further Information

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Gear Oil 150 F

Revision date: 10.05.2023

Product code: 741121

Page 10 of 10

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)