

# Safety Data Sheet

according to UK REACH Regulation

## ADDINOL Eco Gas 4205 XD

Revision date: 02.12.2024

Product code: 725033

Page 1 of 13

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

ADDINOL Eco Gas 4205 XD

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Use of the substance/mixture

Motor oil.

#### 1.3. Details of the supplier of the safety data sheet

##### Manufacturer

Company name:	ADDINOL Lube Oil GmbH	
	Gebäude 4609	
Street:	Am Haupttor	
Place:	D-06237 Leuna	
Telephone:	+49 (0) 3461 845-0	Telefax: +49 (0) 3461 845-555
E-mail:	info@addinol.de	
Contact person:	Application Technology	
Internet:	www.addinol.de	
Responsible Department:	ADDINOL Application Technology	

##### Supplier

Company name:	Gidov Oil & Logistics Ltd.	
Street:	76 Cobham Road, Ferndown Industrial Estate	
Place:	GB-TN157DA Wrotham, Sevenoaks Kent	
Telephone:	+44 7729229830	Telefax: +44 7729229830
E-mail:	sales@addinol.co.uk	
Internet:	<a href="https://www.gidovlogistics.co.uk/">https://www.gidovlogistics.co.uk/</a>	

#### 1.4. Emergency telephone number:

+44 7729229830 - This number is serviced during office hours.

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### GB CLP Regulation

This mixture is not classified as hazardous in accordance with GB CLP Regulation.

#### 2.2. Label elements

##### GB CLP Regulation

##### Special labelling of certain mixtures

EUH210 Safety data sheet available on request.

##### Additional advice on labelling

According to EC directives or the corresponding national regulations the product does not have to be labelled.

#### 2.3. Other hazards

Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

Spilled product must not leak into the ground.

Do not allow uncontrolled leakage of product into the environment.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

## Safety Data Sheet

according to UK REACH Regulation

### ADDINOL Eco Gas 4205 XD

Revision date: 02.12.2024

Product code: 725033

Page 2 of 13

#### Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic			80 - < 100 %
	265-157-1		01-2119484627-25	
	Asp. Tox. 1; H304			
125643-61-0	C7-9-(branched)-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propanoate			2.5 - < 5 %
	406-040-9	607-530-00-7		
	Aquatic Chronic 4; H413			
	Phenol, paraalkylation products with C10-15 branched olefins ( C12 rich) derived from propene oligomerization, calcium salts, sulfurized, including distillates (petroleum), hydrotreated, solvent-refined, solvent-dewaxed, or catalytic dewaxed, light or heavy paraffinic C15-C50			1 - < 2.5 %
	701-249-4		01-2119524018-47	
	Aquatic Chronic 4; H413			
68610-84-4	Benzenesulfonic acid, propenated, calcium salt, overbased			0.3 - < 0.5 %
	271-877-7			
	Skin Sens. 1, Aquatic Chronic 4; H317 H413			
	Benzenesulfonic acid, para-, monoalkylation products with C14-C18 branched olefins (C15 rich) derived from propene oligomerization, calcium salt, overbased including distillates (petroleum), hydrotreated, solvent-refined, solvent-dewaxed, or catalytic dewaxed, light or heavy paraffinic C15-C50			0.1 - < 0.3 %
	701-205-4		01-2119657986-16	
	Skin Sens. 1B, Aquatic Chronic 4; H317 H413			

Full text of H and EUH statements: see section 16.

#### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
64742-54-7	265-157-1	Distillates (petroleum), hydrotreated heavy paraffinic	80 - < 100 %
	dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg		
125643-61-0	406-040-9	C7-9-(branched)-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propanoate	2.5 - < 5 %
	dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 2000 mg/kg		
	701-249-4	Phenol, paraalkylation products with C10-15 branched olefins ( C12 rich) derived from propene oligomerization, calcium salts, sulfurized, including distillates (petroleum), hydrotreated, solvent-refined, solvent-dewaxed, or catalytic dewaxed, light or heavy paraffinic C15-C50	1 - < 2.5 %
	dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg		
68610-84-4	271-877-7	Benzenesulfonic acid, propenated, calcium salt, overbased	0.3 - < 0.5 %
	Skin Sens. 1; H317: >= 2 - 100		
	701-205-4	Benzenesulfonic acid, para-, monoalkylation products with C14-C18 branched olefins (C15 rich) derived from propene oligomerization, calcium salt, overbased including distillates (petroleum), hydrotreated, solvent-refined, solvent-dewaxed, or catalytic dewaxed, light or heavy paraffinic C15-C50	0.1 - < 0.3 %
	dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg Skin Sens. 1B; H317: >= 2 - 100		

#### Further Information

DMSO-Extract < 3 %; IP 346. Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

#### SECTION 4: First aid measures

# Safety Data Sheet

according to UK REACH Regulation

## ADDINOL Eco Gas 4205 XD

Revision date: 02.12.2024

Product code: 725033

Page 3 of 13

### 4.1. Description of first aid measures

#### General information

Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

#### After inhalation

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist.

#### After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. In case of skin irritation, seek medical treatment.

#### After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

#### After ingestion

Do NOT induce vomiting.

Rinse mouth thoroughly with water. Call a physician immediately.

### 4.2. Most important symptoms and effects, both acute and delayed

No information available.

### 4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

Foam. Extinguishing powder. Carbon dioxide (CO<sub>2</sub>). Atomized water.

#### Unsuitable extinguishing media

High power water jet.

### 5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO<sub>2</sub>). Sulfur oxides. Phosphorus oxides. Nitrogen oxides (NO<sub>x</sub>). carbon black.

### 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

#### Additional information

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray jet to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### General advice

High slip hazard because of leaking or spilled product. Remove all sources of ignition. Wear breathing apparatus if exposed to vapours/dusts/aerosols. Avoid contact with skin, eyes and clothes.

### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Prevent spread over a wide area (e.g. by containment or oil barriers).

### 6.3. Methods and material for containment and cleaning up

#### Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean contaminated articles and floor

# Safety Data Sheet

according to UK REACH Regulation

## ADDINOL Eco Gas 4205 XD

Revision date: 02.12.2024

Product code: 725033

Page 4 of 13

according to the environmental legislation.

### **6.4. Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

Section 12: Ecological Information (non-mandatory)

Disposal: see section 13

## **SECTION 7: Handling and storage**

### **7.1. Precautions for safe handling**

#### **Advice on safe handling**

Work in well-ventilated zones or use proper respiratory protection. Avoid oil mist. If handled uncovered, arrangements with local exhaust ventilation have to be used. Avoid contact with skin, eyes and clothes.

#### **Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking.

#### **Advice on general occupational hygiene**

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

### **7.2. Conditions for safe storage, including any incompatibilities**

#### **Requirements for storage rooms and vessels**

Keep the packing dry and well sealed to prevent contamination and absorption of humidity. Keep container tightly closed in a cool place. Keep/Store only in original container.

#### **Hints on joint storage**

Keep away from food, drink and animal feedingstuffs.

Keep away from: Oxidizing agent

#### **Further information on storage conditions**

Recommended storage temperature: 5 - 40°C

Protect against: heat. UV-radiation/sunlight. frost.

### **7.3. Specific end use(s)**

Motor oil. Further information: see technical data sheet.

## **SECTION 8: Exposure controls/personal protection**

### **8.1. Control parameters**

## Safety Data Sheet

according to UK REACH Regulation

### ADDINOL Eco Gas 4205 XD

Revision date: 02.12.2024

Product code: 725033

Page 5 of 13

#### DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic			
	Worker DNEL, long-term	inhalation	systemic	2,73 mg/m <sup>3</sup>
	Worker DNEL, long-term	inhalation	local	5,58 mg/m <sup>3</sup>
	Worker DNEL, long-term	dermal	systemic	0,97 mg/kg bw/day
	Consumer DNEL, long-term	inhalation	local	1,19 mg/m <sup>3</sup>
	Consumer DNEL, long-term	oral	systemic	0,74 mg/kg bw/day
125643-61-0	C7-9-(branched)-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propanoate			
	Worker DNEL, long-term	inhalation	systemic	3 mg/m <sup>3</sup>
	Worker DNEL, long-term	dermal	systemic	8,6 mg/kg bw/day
	Consumer DNEL, long-term	inhalation	systemic	0,74 mg/m <sup>3</sup>
	Consumer DNEL, long-term	dermal	systemic	4,3 mg/kg bw/day
	Consumer DNEL, long-term	oral	systemic	0,43 mg/kg bw/day
	Phenol, paraalkylation products with C10-15 branched olefins ( C12 rich) derived from propene oligomerization, calcium salts, sulfurized, including distillates (petroleum), hydrotreated, solvent-refined, solvent-dewaxed, or catalytic dewaxed, light or heavy paraffinic C15-C50			
	Worker DNEL, long-term	inhalation	systemic	3,5 mg/m <sup>3</sup>
	Worker DNEL, acute	inhalation	systemic	133,6 mg/m <sup>3</sup>
	Worker DNEL, long-term	dermal	systemic	8,33 mg/kg bw/day
	Worker DNEL, acute	dermal	systemic	80 mg/kg bw/day
	Consumer DNEL, long-term	inhalation	systemic	0,87 mg/m <sup>3</sup>
	Consumer DNEL, acute	inhalation	systemic	0,067 mg/m <sup>3</sup>
	Consumer DNEL, long-term	dermal	systemic	4,2 mg/kg bw/day
	Consumer DNEL, acute	dermal	systemic	40 mg/kg bw/day
	Consumer DNEL, long-term	oral	systemic	0,25 mg/kg bw/day
	Consumer DNEL, acute	oral	systemic	50 mg/kg bw/day
	Benzenesulfonic acid, para-, monoalkylation products with C14-C18 branched olefins (C15 rich) derived from propene oligomerization, calcium salt, overbased including distillates (petroleum), hydrotreated, solvent-refined, solvent-dewaxed, or catalytic dewaxed, light or heavy paraffinic C15-C50			
	Worker DNEL, long-term	dermal	systemic	8,33 mg/kg bw/day
	Worker DNEL, acute	dermal	systemic	100 mg/kg bw/day
	Consumer DNEL, long-term	inhalation	systemic	11,8 mg/m <sup>3</sup>
	Consumer DNEL, acute	inhalation	systemic	267,2 mg/m <sup>3</sup>
	Consumer DNEL, long-term	dermal	systemic	4,17 mg/kg bw/day
	Consumer DNEL, acute	dermal	systemic	50 mg/kg bw/day
	Consumer DNEL, long-term	oral	systemic	1,7 mg/kg bw/day
	Worker DNEL, long-term	inhalation	systemic	25,55 mg/m <sup>3</sup>
	Worker DNEL, acute	inhalation	systemic	668 mg/m <sup>3</sup>

## Safety Data Sheet

according to UK REACH Regulation

### ADDINOL Eco Gas 4205 XD

Revision date: 02.12.2024

Product code: 725033

Page 6 of 13

#### PNEC values

CAS No	Substance	Value
Environmental compartment		
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic	
Secondary poisoning		9,33 mg/kg
125643-61-0	C7-9-(branched)-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propanoate	
Freshwater sediment		0,37 mg/kg
Marine sediment		0,037 mg/kg
Micro-organisms in sewage treatment plants (STP)		10 mg/l
Soil		0,632 mg/kg
Phenol, paraalkylation products with C10-15 branched olefins ( C12 rich) derived from propene oligomerization, calcium salts, sulfurized, including distillates (petroleum), hydrotreated, solvent-refined, solvent-dewaxed, or catalytic dewaxed, light or heavy paraffinic C15-C50		
Freshwater		1 mg/l
Freshwater (intermittent releases)		10 mg/l
Marine water		0,1 mg/l
Freshwater sediment		1650 mg/kg
Marine sediment		165 mg/kg
Secondary poisoning		11,11 mg/kg
Micro-organisms in sewage treatment plants (STP)		100 mg/l
Soil		1340 mg/kg
Benzenesulfonic acid, para-, monoalkylation products with C14-C18 branched olefins (C15 rich) derived from propene oligomerization, calcium salt, overbased including distillates (petroleum), hydrotreated, solvent-refined, solvent-dewaxed, or catalytic dewaxed, light or heavy paraffinic C15-C50		
Freshwater		1 mg/l
Freshwater (intermittent releases)		10 mg/l
Marine water		1 mg/l
Freshwater sediment		43500 mg/kg
Marine sediment		3480 mg/kg
Secondary poisoning		33,333 mg/kg
Micro-organisms in sewage treatment plants (STP)		1000 mg/l
Soil		8850 mg/kg

#### Additional advice on limit values

Recommended limit value for oil mist

TWA: 5 mg/m<sup>3</sup>

STEL: 10 mg/m<sup>3</sup>

The product does not contain any relevant quantities of substances with legally established exposure limitation.

#### 8.2. Exposure controls



#### Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

#### Individual protection measures, such as personal protective equipment

**Safety Data Sheet**

according to UK REACH Regulation

**ADDINOL Eco Gas 4205 XD**

Revision date: 02.12.2024

Product code: 725033

Page 7 of 13

**Eye/face protection**

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): DIN EN ISO 16321

**Hand protection**

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): EN ISO 374

Duration of wearing with permanent contact: 480 min

Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.7 mm.

Wearing time with occasional contact (splashes): 30 min

Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.4 mm

Protect skin by using skin protective cream.

**Skin protection**

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

**Respiratory protection**

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Breathing protection with filter against organic gases and vapours type A - boiling point > 65°C: A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Physical state:	liquid
Colour:	yellow - brown
Odour:	characteristic

	Test method
Melting point/freezing point:	No data available
Boiling point or initial boiling point and boiling range:	No data available
Flammability:	No data available
Lower explosion limits:	No data available
Upper explosion limits:	No data available
Flash point:	275 °C DIN EN ISO 2592
Auto-ignition temperature:	No data available
Decomposition temperature:	not determined
pH-Value:	not applicable
Viscosity / kinematic: (at 100 °C)	12,8 mm <sup>2</sup> /s ASTM D 7042
Water solubility:	virtually insoluble
Solubility in other solvents	
No data available	
Partition coefficient n-octanol/water:	No data available
Vapour pressure:	not determined
Density (at 15 °C):	0,875 g/cm <sup>3</sup> DIN 51757
Relative vapour density:	No data available
Particle characteristics:	No data available

**9.2. Other information****Information with regard to physical hazard classes**

# Safety Data Sheet

according to UK REACH Regulation

## ADDINOL Eco Gas 4205 XD

Revision date: 02.12.2024

Product code: 725033

Page 8 of 13

**Explosive properties**

No data available

**Self-ignition temperature**

Solid:

not determined

Gas:

not determined

**Oxidizing properties**

No data available

**Other safety characteristics**

Evaporation rate:

No data available

Pour point:

-18 °C ASTM D 7346

### SECTION 10: Stability and reactivity

**10.1. Reactivity**

The product is stable under storage at normal ambient temperatures.

**10.2. Chemical stability**

The mixture is chemically stable under recommended conditions of storage, use and temperature.

**10.3. Possibility of hazardous reactions**

No known hazardous reactions.

**10.4. Conditions to avoid**

Refer to chapter 7 No further action is necessary.

Do not overheat to avoid decomposition by heat.

**10.5. Incompatible materials**

Reacts with: Oxidising agent, strong

**10.6. Hazardous decomposition products**In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO<sub>2</sub>). Sulfur oxides. Phosphorus oxides.  
Nitrogen oxides (NO<sub>x</sub>). carbon black.

### SECTION 11: Toxicological information

**11.1. Information on hazard classes as defined in GB CLP Regulation****Acute toxicity**

Based on available data, the classification criteria are not met.

Mixture not tested.

**ATEmix calculated**

ATE (oral) &gt; 2000 mg/kg; ATE (dermal) &gt; 2000 mg/kg; ATE (inhalation vapour) &gt; 20 mg/l; ATE (inhalation dust/mist) &gt; 5 mg/l



## Safety Data Sheet

according to UK REACH Regulation

### ADDINOL Eco Gas 4205 XD

Revision date: 02.12.2024

Product code: 725033

Page 9 of 13

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1982)	OECD Guideline 401
	dermal	LD50 > 5000 mg/kg	Rabbit	Study report (1982)	OECD Guideline 402
125643-61-0	C7-9-(branched)-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propanoate				
	oral	LD50 > 2000 mg/kg	Rat	Study report (1989)	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rat	Study report (1989)	OECD Guideline 402
	Phenol, paraalkylation products with C10-15 branched olefins ( C12 rich) derived from propene oligomerization, calcium salts, sulfurized, including distillates (petroleum), hydrotreated, solvent-refined, solvent-dewaxed, or catalytic dewaxed, light or heavy paraffinic C15-C50				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1997)	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rat	Study report (1997)	OECD Guideline 402
	Benzenesulfonic acid, para-, monoalkylation products with C14-C18 branched olefins (C15 rich) derived from propene oligomerization, calcium salt, overbased including distillates (petroleum), hydrotreated, solvent-refined, solvent-dewaxed, or catalytic dewaxed, light or heavy paraffinic C15-C50				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1998)	OECD Guideline 423
	dermal	LD50 > 5000 mg/kg	Rat	Study report (1998)	OECD Guideline 402

#### Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

#### Sensitising effects

Based on available data, the classification criteria are not met.

#### Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

#### STOT-single exposure

Based on available data, the classification criteria are not met.

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

#### Aspiration hazard

Based on available data, the classification criteria are not met.

### 11.2. Information on other hazards

#### Endocrine disrupting properties

not applicable

## SECTION 12: Ecological information

### 12.1. Toxicity

Based on available data, the classification criteria are not met.

## Safety Data Sheet

according to UK REACH Regulation

### ADDINOL Eco Gas 4205 XD

Revision date: 02.12.2024

Product code: 725033

Page 10 of 13

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic					
	Acute fish toxicity	LL50 > 100 mg/l	96 h	Pimephales promelas	Study report (1995)	OECD Guideline 203
	Acute algae toxicity	ErC50 >100 mg/l	72 h			
	Fish toxicity	NOEC >= 1000 mg/l	14 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)	The aquatic toxicity was estimated by a
125643-61-0	C7-9-(branched)-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propanoate					
	Acute fish toxicity	LC50 > 74 mg/l	96 h	Danio rerio	Study report (1989)	OECD Guideline 203
	Acute algae toxicity	ErC50 > 3 mg/l	72 h	Desmodesmus subspicatus	Study report (1995)	OECD Guideline 201
	Acute crustacea toxicity	EC50 > 100 mg/l	48 h	Daphnia magna	Study report (2002)	OECD Guideline 202
	Fish toxicity	NOEC >= 0,001 mg/l	36 d	Danio rerio	Study report (2007)	OECD Guideline 210
	Crustacea toxicity	NOEC 0,3 mg/l	21 d	Daphnia magna	Study report (1995)	EU Method C.20
	Acute bacteria toxicity	EC50 > 100 mg/l ( )	3 h	activated sludge, domestic	Study report (1989)	OECD Guideline 209
	Phenol, paraalkylation products with C10-15 branched olefins ( C12 rich) derived from propene oligomerization, calcium salts, sulfurized, including distillates (petroleum), hydrotreated, solvent-refined, solvent-dewaxed, or catalytic dewaxed, light or heavy paraffinic C15-C50					
	Acute fish toxicity	LL50 > 1000 mg/l	96 h	Oncorhynchus mykiss	REACH Registration Dossier	OECD Guideline 203
	Acute algae toxicity	ErC50 > 1000 mg/l	96 h	Raphidocelis subcapitata	REACH Registration Dossier	OECD Guideline 201
	Acute crustacea toxicity	EL50 > 1000 mg/l	48 h	Daphnia magna	REACH Registration Dossier	OECD Guideline 202
	Benzenesulfonic acid, para-, monoalkylation products with C14-C18 branched olefins (C15 rich) derived from propene oligomerization, calcium salt, overbased including distillates (petroleum), hydrotreated, solvent-refined, solvent-dewaxed, or catalytic dewaxed, light or heavy paraffinic C15-C50					
	Acute fish toxicity	LL50 > 100 mg/l	96 h	Oncorhynchus mykiss	Study report (2005)	OECD Guideline 203
	Acute algae toxicity	ErC50 > 100 mg/l	72 h	Desmodesmus subspicatus	Study report (2005)	OECD Guideline 201
	Acute crustacea toxicity	EL50 > 1000 mg/l	48 h	Daphnia magna	Study report (1993)	EPA OTS 797.1300
	Acute bacteria toxicity	EC50 > 10000 mg/l ( )	3 h	activated sludge of a predominantly domestic sewage	Study report (1997)	OECD Guideline 209

#### 12.2. Persistence and degradability

Not easily bio-degradable (according to OECD-criteria). Do not allow to enter into surface water or drains.

#### 12.3. Bioaccumulative potential

No data available

## Safety Data Sheet

according to UK REACH Regulation

### ADDINOL Eco Gas 4205 XD

Revision date: 02.12.2024

Product code: 725033

Page 11 of 13

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
125643-61-0	C7-9-(branched)-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propanoate	8,5
	Phenol, paraalkylation products with C10-15 branched olefins ( C12 rich) derived from propene oligomerization, calcium salts, sulfurized, including distillates (petroleum), hydrotreated, solvent-refined, solvent-dewaxed, or catalytic dewaxed, light or heavy paraffinic C15-C50	9,8
	Benzenesulfonic acid, para-, monoalkylation products with C14-C18 branched olefins (C15 rich) derived from propene oligomerization, calcium salt, overbased including distillates (petroleum), hydrotreated, solvent-refined, solvent-dewaxed, or catalytic dewaxed, light or heavy paraffinic C15-C50	ca. 5,8

#### BCF

CAS No	Chemical name	BCF	Species	Source
125643-61-0	C7-9-(branched)-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propanoate	258	Oncorhynchus mykiss	Study report (2006)
	Phenol, paraalkylation products with C10-15 branched olefins ( C12 rich) derived from propene oligomerization, calcium salts, sulfurized, including distillates (petroleum), hydrotreated, solvent-refined, solvent-dewaxed, or catalytic dewaxed, light or heavy paraffinic C15-C50	2,2	lipid triolein	Tribology – Solving
	Benzenesulfonic acid, para-, monoalkylation products with C14-C18 branched olefins (C15 rich) derived from propene oligomerization, calcium salt, overbased including distillates (petroleum), hydrotreated, solvent-refined, solvent-dewaxed, or catalytic dewaxed, light or heavy paraffinic C15-C50	45	Oncorhynchus mykiss	Study report (2010)

#### 12.4. Mobility in soil

Due to its low solubility in water the product is almost completely mechanically separated in biological waste water treatment plants.

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

#### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

#### 12.7. Other adverse effects

No data available

#### Further information

Do not allow uncontrolled leakage of product into the environment.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

##### Disposal recommendations

Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

##### List of Wastes Code - residues/unused products

130205 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; mineral-based non-chlorinated engine, gear and lubricating oils; hazardous waste

# Safety Data Sheet

according to UK REACH Regulation

**ADDINOL Eco Gas 4205 XD**

Revision date: 02.12.2024

Product code: 725033

Page 12 of 13

**Contaminated packaging**

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Dispose of waste according to applicable legislation. Packing which cannot be properly cleaned must be thrown away.

**SECTION 14: Transport information****Land transport (ADR/RID)**

- 14.1. UN number or ID number:** -  
**14.2. UN proper shipping name:** -  
**14.3. Transport hazard class(es):** -  
**14.4. Packing group:** -

**Inland waterways transport (ADN)**

- 14.1. UN number or ID number:** -  
**14.2. UN proper shipping name:** -  
**14.3. Transport hazard class(es):** -  
**14.4. Packing group:** -

**Marine transport (IMDG)**

- 14.1. UN number or ID number:** -  
**14.2. UN proper shipping name:** -  
**14.3. Transport hazard class(es):** -  
**14.4. Packing group:** -

**Air transport (ICAO-TI/IATA-DGR)**

- 14.1. UN number or ID number:** -  
**14.2. UN proper shipping name:** -  
**14.3. Transport hazard class(es):** -  
**14.4. Packing group:** -

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

**14.6. Special precautions for user**

Unless specified otherwise, general measures for safe transport must be followed.

**14.7. Maritime transport in bulk according to IMO instruments**

not applicable

**Other applicable information**

No dangerous good in sense of these transport regulations.

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****National regulatory information**

Water hazard class (D): 1 - slightly hazardous to water

**15.2. Chemical safety assessment**

Chemical safety assessments for substances in this mixture were not carried out.

**SECTION 16: Other information****Changes**

This data sheet contains changes from the previous version in section(s): 2,3,5,7,8,9,10,12,13.

**Safety Data Sheet**

according to UK REACH Regulation

**ADDINOL Eco Gas 4205 XD**

Revision date: 02.12.2024

Product code: 725033

Page 13 of 13

**Abbreviations and acronyms**

Asp. Tox: Aspiration hazard

Skin Sens: Skin sensitisation

Aquatic Chronic: Chronic aquatic hazard

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ASTM - American Society for the Testing of Materials; ATE - Acute Toxicity Estimates; bw - Body weight; CAO - Cargo Aircraft Only; CAS - Chemical Abstracts Service; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DNEL - Derived No-Effect Level; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); EG - European Union; EN - European standards; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISO - International Organisation for Standardization; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n; o; s; - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; OECD - Organization for Economic Co-operation and Development; PBT - Persistent, Bioaccumulative and Toxic substance; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulation concerning the International Carriage of Dangerous Goods by Rail; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

**Relevant H and EUH statements (number and full text)**

H304	May be fatal if swallowed and enters airways.
H317	May cause an allergic skin reaction.
H413	May cause long lasting harmful effects to aquatic life.
EUH210	Safety data sheet available on request.

**Further Information**

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*