

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Hydrodynamic Transmission Oil SGL 18

Revision date: 12.06.2024

Product code: 759001

Page 2 of 14

2.3. Other hazards

Prolonged/repetitive skin contact may cause skin defatting or dermatitis.
Spilled product must not leak into the ground.
Do not allow uncontrolled leakage of product into the environment.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Relevant ingredients

CAS No	Chemical name	Quantity
	EC No	
	Index No	
	REACH No	
	Classification (GB CLP Regulation)	
64742-56-9	Distillates (petroleum), solvent-dewaxed light paraffinic; base oil - not specified	60 - < 80 %
	265-159-2	
	01-2119480132-48	
	Asp. Tox. 1; H304	
128-37-0	2,6-di-tert-butyl-4-methylphenol	0.3 - < 0.5 %
	204-881-4	
	01-2119555270-46	
	Aquatic Chronic 1; H410	
722503-68-6	Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts	0.1 - < 0.3 %
	682-816-2	
	01-2119985162-35	
	Skin Sens. 1B; H317	
121158-58-5	phenol, dodecyl-, branched	< 0.1 %
	310-154-3	
	604-092-00-9	
	01-2119513207-49	
	Repr. 1B, Skin Corr. 1C, Eye Dam. 1, Aquatic Acute 1, Aquatic Chronic 1; H360F H314 H318 H400 H410	
25307-17-9	2,2'-(octadec-9-enylimino)bisethanol	< 0.1 %
	246-807-3	
	01-2119510876-35	
	Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1, Aquatic Acute 1, Aquatic Chronic 1; H302 H314 H318 H400 H410	
107-21-1	ethanediol; ethylene glycol	< 0.1 %
	203-473-3	
	603-027-00-1	
	Acute Tox. 4, STOT RE 2; H302 H373	

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
64742-56-9	265-159-2	Distillates (petroleum), solvent-dewaxed light paraffinic; base oil - not specified	60 - < 80 %
		dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg	
128-37-0	204-881-4	2,6-di-tert-butyl-4-methylphenol	0.3 - < 0.5 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 6000 mg/kg Aquatic Chronic 1; H410: M=1	
121158-58-5	310-154-3	phenol, dodecyl-, branched	< 0.1 %
		Aquatic Acute 1; H400: M=10 Aquatic Chronic 1; H410: M=10	
25307-17-9	246-807-3	2,2'-(octadec-9-enylimino)bisethanol	< 0.1 %
		oral: LD50 = 1260 mg/kg Aquatic Acute 1; H400: M=10 Aquatic Chronic 1; H410: M=1	
107-21-1	203-473-3	ethanediol; ethylene glycol	< 0.1 %
		dermal: LD50 = 10600 mg/kg; oral: ATE = 500 mg/kg	

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Hydrodynamic Transmission Oil SGL 18

Revision date: 12.06.2024

Product code: 759001

Page 3 of 14

Further Information

DMSO-Extract < 3 %; IP 346. Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

After inhalation

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. In case of skin irritation, seek medical treatment.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

After ingestion

Do NOT induce vomiting.

Rinse mouth thoroughly with water. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂). Extinguishing powder. Water spray. alcohol resistant foam.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO₂). Sulfur oxides. Phosphorus oxides. Nitrogen oxides (NO_x). carbon black

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray jet to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. In case of fire: Wear self-contained breathing apparatus. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

High slip hazard because of leaking or spilled product. Remove all sources of ignition. Wear breathing apparatus if exposed to vapours/dusts/aerosols. Avoid contact with skin, eyes and clothes.

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Hydrodynamic Transmission Oil SGL 18

Revision date: 12.06.2024

Product code: 759001

Page 4 of 14

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Prevent spread over a wide area (e.g. by containment or oil barriers).

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Section 12: Ecological Information (non-mandatory)

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Work in well-ventilated zones or use proper respiratory protection. Avoid oil mist. If handled uncovered, arrangements with local exhaust ventilation have to be used. Avoid contact with skin, eyes and clothes.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Advice on general occupational hygiene

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep the packing dry and well sealed to prevent contamination and absorption of humidity. Keep container tightly closed in a cool place. Keep/Store only in original container.

Hints on joint storage

Keep away from food, drink and animal feedingstuffs.

Keep away from: Oxidizing agent

Further information on storage conditions

Recommended storage temperature: 5 - 40°C

Protect against: heat. UV-radiation/sunlight. frost.

7.3. Specific end use(s)

Further information: see technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
128-37-0	2,6-Di-tert-butyl-p-cresol	-	10		TWA (8 h)	WEL
107-21-1	Ethane-1,2-diol, vapour	20	52		TWA (8 h)	WEL
		40	104		STEL (15 min)	WEL

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Hydrodynamic Transmission Oil SGL 18

Revision date: 12.06.2024

Product code: 759001

Page 5 of 14

DNEL/DMEL values

CAS No	Substance		
DNEL type	Exposure route	Effect	Value
64742-56-9	Distillates (petroleum), solvent-dewaxed light paraffinic; base oil - not specified		
Worker DNEL, long-term	inhalation	systemic	2,73 mg/m ³
Worker DNEL, long-term	inhalation	local	5,58 mg/m ³
Worker DNEL, long-term	dermal	systemic	0,97 mg/kg bw/day
Consumer DNEL, long-term	inhalation	local	1,19 mg/m ³
Consumer DNEL, long-term	oral	systemic	0,74 mg/kg bw/day
128-37-0	2,6-di-tert-butyl-4-methylphenol		
Worker DNEL, long-term	inhalation	systemic	1,76 mg/m ³
Worker DNEL, long-term	dermal	systemic	0,5 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	0,435 mg/m ³
Consumer DNEL, long-term	dermal	systemic	0,25 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	0,25 mg/kg bw/day
121158-58-5	phenol, dodecyl-, branched		
Worker DNEL, acute	inhalation	systemic	44,18 mg/m ³
Worker DNEL, long-term	dermal	systemic	0,25 mg/kg bw/day
Worker DNEL, acute	dermal	systemic	166 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	0,79 mg/m ³
Consumer DNEL, acute	inhalation	systemic	13,26 mg/m ³
Consumer DNEL, long-term	dermal	systemic	0,075 mg/kg bw/day
Consumer DNEL, acute	dermal	systemic	50 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	0,075 mg/kg bw/day
Consumer DNEL, acute	oral	systemic	1,26 mg/kg bw/day
25307-17-9	2,2'-(octadec-9-enylimino)bisethanol		
Consumer DNEL, long-term	oral	systemic	0,15 mg/kg bw/day
Worker DNEL, long-term	inhalation	systemic	2,96 mg/m ³
Worker DNEL, long-term	dermal	systemic	0,42 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	0,522 mg/m ³
Consumer DNEL, long-term	dermal	systemic	0,15 mg/kg bw/day
107-21-1	ethanediol; ethylene glycol		
Worker DNEL, long-term	inhalation	local	35 mg/m ³
Worker DNEL, long-term	dermal	systemic	106 mg/kg bw/day
Consumer DNEL, long-term	inhalation	local	7 mg/m ³
Consumer DNEL, long-term	dermal	systemic	53 mg/kg bw/day

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Hydrodynamic Transmission Oil SGL 18

Revision date: 12.06.2024

Product code: 759001

Page 6 of 14

PNEC values

CAS No	Substance	Value
Environmental compartment		
64742-56-9	Distillates (petroleum), solvent-dewaxed light paraffinic; base oil - not specified	
Secondary poisoning		9,33 mg/kg
128-37-0	2,6-di-tert-butyl-4-methylphenol	
Freshwater		0,000199 mg/l
Freshwater (intermittent releases)		0,00199 mg/l
Marine water		0,00002 mg/l
Freshwater sediment		0,458 mg/kg
Marine sediment		0,046 mg/kg
Secondary poisoning		16,67 mg/kg
Micro-organisms in sewage treatment plants (STP)		0,017 mg/l
Soil		0,054 mg/kg
121158-58-5	phenol, dodecyl-, branched	
Freshwater		0,000074 mg/l
Freshwater (intermittent releases)		0,00037 mg/l
Marine water		0,000007 mg/l
Freshwater sediment		0,226 mg/kg
Marine sediment		0,027 mg/kg
Secondary poisoning		4 mg/kg
Micro-organisms in sewage treatment plants (STP)		100 mg/l
Soil		0,118 mg/kg
25307-17-9	2,2'-(octadec-9-enylimino)bisethanol	
Freshwater		0,000214 mg/l
Freshwater (intermittent releases)		0,00087 mg/l
Marine water		0,000021 mg/l
Freshwater sediment		1,692 mg/kg
Marine sediment		0,169 mg/kg
Secondary poisoning		2 mg/kg
Micro-organisms in sewage treatment plants (STP)		1,5 mg/l
Soil		5 mg/kg

Additional advice on limit values

Recommended limit value for oil mist

TWA: 5 mg/m³

STEL: 10 mg/m³

The product does not contain any relevant quantities of substances with legally established exposure limitation.

8.2. Exposure controls



Safety Data Sheet

according to UK REACH Regulation

ADDINOL Hydrodynamic Transmission Oil SGL 18

Revision date: 12.06.2024

Product code: 759001

Page 7 of 14

Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): EN 166

Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): EN ISO 374

Duration of wearing with permanent contact: 480 min

Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.7 mm.

Wearing time with occasional contact (splashes): 30 min

Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.4 mm

Protect skin by using skin protective cream.

Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Breathing protection with filter against organic gases and vapours type A - boiling point > 65°C: A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	liquid
Colour:	brown
Odour:	like: mineral oil.
Odour threshold:	not determined

	Test method
Melting point/freezing point:	No data available
Boiling point or initial boiling point and boiling range:	No data available
Flammability:	No data available
Lower explosion limits:	No data available
Upper explosion limits:	No data available
Flash point:	228 °C DIN EN ISO 2592
Auto-ignition temperature:	No data available
Decomposition temperature:	No data available
pH-Value:	not applicable
Viscosity / kinematic: (at 40 °C)	32 mm ² /s ASTM D 7042
Water solubility:	virtually insoluble
Solubility in other solvents	
No data available	
Partition coefficient n-octanol/water:	No data available
Vapour pressure:	No data available
Density (at 15 °C):	0,877 g/cm ³ DIN 51757
Relative vapour density:	No data available

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Hydrodynamic Transmission Oil SGL 18

Revision date: 12.06.2024

Product code: 759001

Page 8 of 14

Particle characteristics:

No data available

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

No data available

Self-ignition temperature

Solid:

No data available

Gas:

No data available

Oxidizing properties

No data available

Other safety characteristics

Evaporation rate:

No data available

Pour point:

-39 °C ASTM D 7346

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Refer to chapter 7 No further action is necessary.

Do not overheat to avoid decomposition by heat.

10.5. Incompatible materials

Reacts with: Oxidising agent, strong. Acid.

10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO₂). Sulfur oxides. Phosphorus oxides.Nitrogen oxides (NO_x). carbon black

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

Mixture not tested.

ATE_{mix} calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Hydrodynamic Transmission Oil SGL 18

Revision date: 12.06.2024

Product code: 759001

Page 9 of 14

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-56-9	Distillates (petroleum), solvent-dewaxed light paraffinic; base oil - not specified				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1982)	OECD Guideline 401
	dermal	LD50 > 5000 mg/kg	Rabbit	Study report (1982)	OECD Guideline 402
128-37-0	2,6-di-tert-butyl-4-methylphenol				
	oral	LD50 > 6000 mg/kg	Rat	Study report (1989)	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rat	Study report (1988)	OECD Guideline 402
25307-17-9	2,2'-(octadec-9-enylimino)bisethanol				
	oral	LD50 1260 mg/kg	Rat	Study report (1987)	OECD Guideline 401
107-21-1	ethanediol; ethylene glycol				
	oral	ATE 500 mg/kg			
	dermal	LD50 10600 mg/kg	Rabbit	GESTIS	

Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Contains Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts. May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards**Endocrine disrupting properties**

not applicable

SECTION 12: Ecological information**12.1. Toxicity**

Harmful to aquatic life with long lasting effects.

Mixture not tested.

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Hydrodynamic Transmission Oil SGL 18

Revision date: 12.06.2024

Product code: 759001

Page 10 of 14

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
64742-56-9	Distillates (petroleum), solvent-dewaxed light paraffinic; base oil - not specified					
	Acute fish toxicity	LL50 mg/l	> 100	96 h	Pimephales promelas	Study report (1995) OECD Guideline 203
	Fish toxicity	NOEC mg/l	>= 1000	14 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010) The aquatic toxicity was estimated by a
128-37-0	2,6-di-tert-butyl-4-methylphenol					
	Acute fish toxicity	LC50 mg/l	0,199	96 h	Oryzias latipes	REACH Registration Dossier OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	0,758	96 h	Pseudokirchneriella subcapitata	REACH Registration Dossier OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	0,48	48 h	Daphnia magna	REACH Registration Dossier OECD Guideline 202
	Fish toxicity	NOEC mg/l	0,053	30 d	Oryzias latipes	REACH Registration Dossier OECD Guideline 210
	Crustacea toxicity	NOEC mg/l	0,069	21 d	Daphnia magna	REACH Registration Dossier OECD Guideline 211
	Acute bacteria toxicity	EC50 mg/l ()	> 10000	3 h	Activated sludge	Study report (2000) OECD Guideline 209
25307-17-9	2,2'-(octadec-9-enylimino)bisethanol					
	Acute fish toxicity	LC50	0,6 mg/l	96 h	Danio rerio	Study report (1990) OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	0,0867	72 h	Pseudokirchneriella subcapitata	Study report (2010) OECD Guideline 201
	Acute bacteria toxicity	EC50 ()	167 mg/l	3 h	activated sludge of a predominantly domestic sewage	Study report (2010) OECD Guideline 209

12.2. Persistence and degradability

Not easily bio-degradable (according to OECD-criteria). Do not allow to enter into surface water or drains.

12.3. Bioaccumulative potential

No data available

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
128-37-0	2,6-di-tert-butyl-4-methylphenol	5,03
25307-17-9	2,2'-(octadec-9-enylimino)bisethanol	3,4
107-21-1	ethanediol; ethylene glycol	-1,36

BCF

CAS No	Chemical name	BCF	Species	Source
128-37-0	2,6-di-tert-butyl-4-methylphenol	465	Fish	REACH Registration D
25307-17-9	2,2'-(octadec-9-enylimino)bisethanol	1,37		QSAR result (2010)

12.4. Mobility in soil

Due to its low solubility in water the product is almost completely mechanically separated in biological waste water treatment plants.

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Hydrodynamic Transmission Oil SGL 18

Revision date: 12.06.2024

Product code: 759001

Page 11 of 14

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No data available

Further information

Do not allow uncontrolled leakage of product into the environment.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

List of Wastes Code - residues/unused products

130205 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; mineral-based non-chlorinated engine, gear and lubricating oils; hazardous waste

Contaminated packaging

Waste requires monitoring. Contaminated packages must be completely emptied and can be re-used following proper cleaning. Packing which cannot be properly cleaned must be thrown away. Dispose of waste according to applicable legislation.

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number or ID number: -
14.2. UN proper shipping name: -
14.3. Transport hazard class(es): -
14.4. Packing group: -

Inland waterways transport (ADN)

14.1. UN number or ID number: -
14.2. UN proper shipping name: -
14.3. Transport hazard class(es): -
14.4. Packing group: -

Marine transport (IMDG)

14.1. UN number or ID number: -
14.2. UN proper shipping name: -
14.3. Transport hazard class(es): -
14.4. Packing group: -

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: -
14.2. UN proper shipping name: -
14.3. Transport hazard class(es): -
14.4. Packing group: -

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Maritime transport in bulk according to IMO instruments

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Hydrodynamic Transmission Oil SGL 18

Revision date: 12.06.2024

Product code: 759001

Page 12 of 14

not applicable

Other applicable information

No dangerous good in sense of these transport regulations.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Authorisations (REACH, annex XIV):

Substances of very high concern, SVHC (REACH, article 59):
phenol, dodecyl-, branched

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 75

National regulatory information

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,3,5,6,7,8,9,10,11,12.

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Hydrodynamic Transmission Oil SGL 18

Revision date: 12.06.2024

Product code: 759001

Page 13 of 14

Abbreviations and acronyms

Acute Tox: Acute toxicity

Asp. Tox: Aspiration hazard

Skin Corr: Skin corrosion

Eye Dam: Eye damage

Skin Sens: Skin sensitisation

Repr: Reproductive toxicity

STOT RE: Specific target organ toxicity - repeated exposure

Aquatic Acute: Acute aquatic hazard

Aquatic Chronic: Chronic aquatic hazard

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ASTM - American Society for the Testing of Materials; ATE - Acute Toxicity Estimates; bw - Body weight; CAO - Cargo Aircraft Only; CAS - Chemical Abstracts Service; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DNEL - Derived No-Effect Level; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); EG - European Union; EN - European standards; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISO - International Organisation for Standardization; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n;o;s; - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; OECD - Organization for Economic Co-operation and Development; PBT - Persistent, Bioaccumulative and Toxic substance; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulation concerning the International Carriage of Dangerous Goods by Rail; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H360F	May damage fertility.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH208	Contains Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts. May produce an allergic reaction.

Further Information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Hydrodynamic Transmission Oil SGL 18

Revision date: 12.06.2024

Product code: 759001

Page 14 of 14

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)