according to Regulation (EC) No 1907/2006

ADDINOL Lube Oil RL 3					
Revision date: 15.04.2025	Product code: 765004		Page 1 of 11		
SECTION 1: Identification of the s	ubstance/mixture and of the compar	ny/undertaking			
<u>1.1. Product identifier</u> ADDINOL Lube Oil RL 3					
UFI:	P1PA-F6RK-620Y-0ED0				
1.2. Relevant identified uses of the su	ubstance or mixture and uses advised a	<u>gainst</u>			
Use of the substance/mixture					
Lubricant and additive.					
1.3. Details of the supplier of the safe	ety data sheet				
Manufacturer					
Company name:	ADDINOL Lube Oil GmbH Gebäude 4609				
Street:	Am Haupttor				
Place:	D-06237 Leuna				
Telephone:	+49 (0) 3461 845-0	Telefax:+49 (0) 3461 845-555			
E-mail:	info@addinol.de				
Contact person: Internet:	Application Technology www.addinol.de				
Responsible Department:	ADDINOL Application Technology				
Supplier	ADDINOL Application reenhology				
Company name: Place:	GEM OILS LIMITED IRL-H12K298 Regaskin Co. Cavan				
Telephone:	+353 49 4378116	Telefax:+353 49 4368329			
E-mail:	sales@gemoils.ie				
Contact person:	GEM OILS LIMITED	Telephone: +353 49 4378116			
E-mail:	sales@gemoils.ie				
Internet:	https://gemoils.ie/				
1.4. Emergency telephone	Healthcare Professionals: +353 (1) 809	2566 (24 hour service)			
<u>number:</u>					
SECTION 2: Hazards identification					

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Asp. Tox. 1; H304

Full text of hazard statements: see SECTION 16.

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling White mineral oil

Signal word:

Pictograms:



Danger

Hazard statements H304

May be fatal if swallowed and enters airways.

according to Regulation (EC) No 1907/2006

ADDINOL Lube Oil RL 3

Revision date: 15.04.2025

Product code: 765004

Page 2 of 11

Precautionary statements

P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331	Do NOT induce vomiting.
P405	Store locked up.
P501	Dispose of contents/container to an appropriate recycling or disposal facility.

Additional advice on labelling

The product is classified and labelled according to EC directives or corresponding national laws.

2.3. Other hazards

Prolonged/repetitive skin contact may cause skin defattening or dermatitis.

Process vapors can irritate airways, skin and eyes.

Do not allow uncontrolled leakage of product into the environment.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture of mineral oil rafffinates and additives.

Relevant ingredients

CAS No	Chemical name	Chemical name		
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No	1272/2008)		
8042-47-5	White mineral oil		80 - < 100 %	
	232-455-8		01-2119487078-27	
	Asp. Tox. 1; H304			
128-37-0	2,6-di-tert-butyl-4-methylphenol		0.1 - < 0.3 %	
	204-881-4		01-2119555270-46	
	Aquatic Chronic 1; H410			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity	
	Specific Conc. I	Limits, M-factors and ATE		
8042-47-5	232-455-8	White mineral oil	80 - < 100 %	
	dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg			
128-37-0	204-881-4	2,6-di-tert-butyl-4-methylphenol	0.1 - < 0.3 %	
	dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 6000 mg/kg Aquatic Chronic 1; H410: M=1			

Further Information

DMSO-Extract < 3 %; IP 346. Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

After inhalation

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. In

according to Regulation (EC) No 1907/2006

ADDINOL Lube Oil RL 3

Revision date: 15.04.2025

Product code: 765004

Page 3 of 11

case of skin irritation, seek medical treatment.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

After ingestion

Do NOT induce vomiting. Rinse mouth thoroughly with water. Call a physician immediately. Caution if victim vomits: Risk of aspiration!

4.2. Most important symptoms and effects, both acute and delayed

The following symptoms may occur: Coughing. difficulties of breathing.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam. Extinguishing powder. Carbon dioxide (CO2). Atomized water. Sand.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO2). Nitrogen oxides (NOx). Sulfur oxides. Phosphorus oxides. carbon black.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray jet to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

High slip hazard because of leaking or spilled product. Remove all sources of ignition. Wear breathing apparatus if exposed to vapours/dusts/aerosols. Avoid contact with skin, eyes and clothes.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Prevent spread over a wide area (e.g. by containment or oil barriers).

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Section 12: Ecological Information (non-mandatory) Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

according to Regulation (EC) No 1907/2006

ADDINOL Lube Oil RL 3

Revision date: 15.04.2025

Product code: 765004

Page 4 of 11

Advice on safe handling

Work in well-ventilated zones or use proper respiratory protection. Avoid oil mist If handled uncovered, arrangements with local exhaust ventilation have to be used. Avoid contact with skin, eyes and clothes.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Provide adequate ventilation. When hot, product develops flammable vapours.

Advice on general occupational hygiene

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep the packing dry and well sealed to prevent contamination and absorbtion of humidity. Keep container tightly closed in a cool place. Keep/Store only in original container.

Hints on joint storage

Keep away from food, drink and animal feedingstuffs. Keep away from: Oxidizing agent

Further information on storage conditions

Recommended storage temperature: 5 - 40°C Protect against: heat. UV-radiation/sunlight. frost.

7.3. Specific end use(s)

Further information: see technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm ³	Category	Origin
128-37-0	2,6-Ditertiary-butyl-para-cresol	-	2		TWA (8 h)	

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
8042-47-5	White mineral oil			
Worker DNEL	., long-term	dermal	systemic	217,05 mg/kg bw/day
Worker DNEL	., long-term	inhalation	systemic	164,56 mg/m ³
Consumer DNEL, long-term		dermal	systemic	93,02 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	34,78 mg/m³
Consumer DN	NEL, long-term	oral	systemic	25 mg/kg bw/day
128-37-0	2,6-di-tert-butyl-4-methylphenol			
Worker DNEL	, long-term	inhalation	systemic	1,76 mg/m³
Worker DNEL	., long-term	dermal	systemic	0,5 mg/kg bw/day
Consumer D	NEL, long-term	inhalation	systemic	0,435 mg/m³
Consumer DNEL, long-term		dermal	systemic	0,25 mg/kg bw/day
Consumer D	NEL, long-term	oral	systemic	0,25 mg/kg bw/day

according to Regulation (EC) No 1907/2006

ADDINOL Lube Oil RL 3

Revision date: 15.04.2025

Product code: 765004

Page 5 of 11

PNEC values

CAS No	Substance	
Environmen	tal compartment	Value
128-37-0	2,6-di-tert-butyl-4-methylphenol	
Freshwater		0,000199 mg/l
Freshwater	(intermittent releases)	0,00199 mg/l
Marine water		0,00002 mg/l
Freshwater	sediment	0,458 mg/kg
Marine sedi	nent	0,046 mg/kg
Secondary p	oisoning	16,67 mg/kg
Micro-organisms in sewage treatment plants (STP)		0,017 mg/l
Soil		0,054 mg/kg

Additional advice on limit values

Recommended limit value for oil mist TWA: 5 mg/m³ STEL: 10 mg/m³

The product does not contain any relevant quantities of substances with legally established exposure limitation.

8.2. Exposure controls





Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.

Individual protection measures, such as personal protective equipment

Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): DIN EN ISO 16321

Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): EN ISO 374

Duration of wearing with permanent contact: 480 min Suitable material: NBR (Nitrile rubber). Thickness of glove material: 0.7 mm.

Wearing time with occasional contact (splashes): 30 min Suitable material: NBR (Nitrile rubber). Thickness of glove material: 0.4 mm

Protect skin by using skin protective cream.

Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Cosaint riospráide le scagaire i gcoinne gás orgánach agus gaile cineál A - fiuchphointe> 65 ° C: A1: <1000 ppm; A2: <5000 ppm; A3: <10,000 ppm.

according to Regulation (EC) No 1907/2006

ADDINOL Lube Oil RL 3

Revision date: 15.04.2025

Product code: 765004

Page 6 of 11

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

9.1. Information on basic physical and che Physical state:	liquid		
Colour:	yellow		
Odour:	like: mineral oil.		
Odour threshold:	not determined		
			Test method
Melting point/freezing point:		No data available	loot motilou
Boiling point or initial boiling point and		No data available	
boiling range:			
Flammability:		No data available	
Lower explosion limits:		No data available	
Upper explosion limits:		No data available	
Flash point:		120 °C	DIN 22719
Auto-ignition temperature:		No data available	
Decomposition temperature:		No data available	
pH-Value:		No data available	
Viscosity / kinematic:		3,8 mm²/s	ASTM D 7042
(at 40 °C)			
Water solubility:		virtually insoluble	
Solubility in other solvents			
No data available			
Partition coefficient n-octanol/water:		No data available	
Vapour pressure:		No data available	
Density (at 15 °C):		0,828 g/cm ³	DIN 51757
Relative vapour density:		No data available	
Particle characteristics:		No data available	
9.2. Other information			
Information with regard to physical haz	ard classes		
Explosive properties			
No data available			
Self-ignition temperature		Ne dete evell-bl-	
Solid:		No data available	
Gas:		No data available	
Oxidizing properties			
No data available			

Other safety characteristics

Evaporation rate: Pour point: No data available -53 °C ASTM D 7346

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Refer to chapter 7 No further action is necessary.

according to Regulation (EC) No 1907/2006

ADDINOL Lube Oil RL 3

Revision date: 15.04.2025

Product code: 765004

Page 7 of 11

Do not overheat to avoid decomposition by heat.

10.5. Incompatible materials

Reacts with :Oxidising agent, strong

10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO2). Nitrogen oxides (NOx). Sulfur oxides. Phosphorus oxides. carbon black.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met. Mixture not tested.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
8042-47-5	White mineral oil					
	oral	LD50 mg/kg	> 5000	Rat	Study report (1987)	OECD Guideline 401
	dermal	LD50 mg/kg	> 2000	Rabbit	Study report (1987)	OECD Guideline 402
128-37-0	2,6-di-tert-butyl-4-methylphenol					
	oral	LD50 mg/kg	> 6000	Rat	Study report (1989)	OECD Guideline 401
	dermal	LD50 mg/kg	> 2000	Rat	Study report (1988)	OECD Guideline 402

Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met. Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met. Carcinogenicity: Based on available data, the classification criteria are not met. Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Prolonged/repetitive skin contact may cause skin defattening or dermatitis.

Aspiration hazard

May be fatal if swallowed and enters airways.

11.2. Information on other hazards

Endocrine disrupting properties

not applicable

according to Regulation (EC) No 1907/2006

ADDINOL Lube Oil RL 3

Revision date: 15.04.2025

Product code: 765004

Page 8 of 11

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met. Mixture not tested.

CAS No	Chemical name							
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method	
8042-47-5	White mineral oil							
	Acute fish toxicity	LL50 mg/l	> 10000	96 h	Leuciscus idus melanotus	Study report (1992)	OECD Guideline 203	
	Acute crustacea toxicity	EL50 mg/l	> 100	48 h	Daphnia magna	Study report (2008)	OECD Guideline 202	
128-37-0	-37-0 2,6-di-tert-butyl-4-methylphenol							
	Acute fish toxicity	LC50 mg/l	0,199	96 h	Oryzias latipes	REACh Registration Dossier	OECD Guideline 203	
	Acute algae toxicity	ErC50 mg/l	0,758	96 h	Pseudokirchneriella subcapitata	REACh Registration Dossier	OECD Guideline 201	
	Acute crustacea toxicity	EC50 mg/l	0,48	48 h	Daphnia magna	REACh Registration Dossier	OECD Guideline 202	
	Fish toxicity	NOEC mg/l	0,053	30 d	Oryzias latipes	REACh Registration Dossier	OECD Guideline 210	
	Crustacea toxicity	NOEC mg/l	0,069	21 d	Daphnia magna	REACh Registration Dossier	OECD Guideline 211	
	Acute bacteria toxicity	EC50 mg/l()	> 10000	3 h	Activated sludge	Study report (2000)	OECD Guideline 209	

12.2. Persistence and degradability

Not easily bio-degradable (according to OECD-criteria). Do not allow to enter into surface water or drains.

12.3. Bioaccumulative potential

No data available

Partition coefficient n-octanol/water

CAS No	Chemical name				Log Pow
128-37-0	2,6-di-tert-butyl-4-methylphenol	2,6-di-tert-butyl-4-methylphenol			5,03
BCF					
CAS No	Chemical name	BCF	Species	Source	
128-37-0	2,6-di-tert-butyl-4-methylphenol	465		REACh Reg	jistration D

12.4. Mobility in soil

Due to its low solubility in water the product is almost completely mechanically separated in biological waste water treatment plants.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

according to Regulation (EC) No 1907/2006

ADDINOL Lube Oil RL 3

Revision date: 15.04.2025

Product code: 765004

Page 9 of 11

No data available

Further information

Do not allow uncontrolled leakage of product into the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

List of Wastes Code - residues/unused products

130205 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; mineral-based non-chlorinated engine, gear and lubricating oils; hazardous waste

Contaminated packaging

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Dispose of waste according to applicable legislation. Packing which cannot be properly cleaned must be thrown away.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:	-
14.2. UN proper shipping name:	-
14.3. Transport hazard class(es):	-
<u>14.4. Packing group:</u>	-
Inland waterways transport (ADN)	
14.1. UN number or ID number:	-
14.2. UN proper shipping name:	-
14.3. Transport hazard class(es):	-
14.4. Packing group:	-
Marine transport (IMDG)	
14.1. UN number or ID number:	-
14.2. UN proper shipping name:	-
14.3. Transport hazard class(es):	-
14.4. Packing group:	-
Air transport (ICAO-TI/IATA-DGR)	
14.1. UN number or ID number:	-
14.2. UN proper shipping name:	-
14.3. Transport hazard class(es):	-
<u>14.4. Packing group:</u>	-
14.5. Environmental hazards	
ENVIRONMENTALLY HAZARDOUS:	No
14.6. Special precautions for user	
Unless specified otherwise, general m	easures for safe transport must be followed.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

Other applicable information

No dangerous good in sense of these transport regulations.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

according to Regulation (EC) No 1907/2006

Revision date: 15.04.2025

Product code: 765004

Page 10 of 11

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3

National regulatory information

Water hazard class (D):

1 - slightly hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,3,5,6,7,8,9,10,11.

Abbreviations and acronyms

Asp. Tox: Aspiration hazard

Aquatic Chronic: Chronic aquatic hazard

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road ; ADN -European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ASTM -American Society for the Testing of Materials; ATE - Acute Toxicity Estimates; bw - Body weight; CAO - Cargo Aircraft Only; CAS - Chemical Abstracts Service; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DNEL - Derived No-Effect Level; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); EG - European Union; EN - European standards; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISO - International Organisation for Standardization; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n;o;s; - Not Otherwise Specified; NFPA -National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; OECD - Organization for Economic Co-operation and Development; PBT - Persistent, Bioaccumulative and Toxic substance; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA -Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulation concerning the International Carriage of Dangerous Goods by Rail; RQ -Reportable Quantity; SADT - Self- Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TSCA - Toxic Substances Control Act (United States); UN -United Nations; vPvB - Very Persistent and Very Bioaccumulative

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Asp. Tox. 1; H304	Calculation method

Relevant H and EUH statements (number and full text)

H304 H410 May be fatal if swallowed and enters airways. Very toxic to aquatic life with long lasting effects.

Further Information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be

according to Regulation (EC) No 1907/2006

ADDINOL Lube Oil RL 3

Revision date: 15.04.2025

Product code: 765004

Page 11 of 11

transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)